

17.1 Description of motion: planar rigid-object kinematics

As a rigid object moves, how do the points on it move? There are two reasons to ask this question. First, velocities and accelerations of mass points are needed to apply the momentum-balance equations. Second, formulas for positions, velocities and accelerations of points are useful to understand *mechanisms*, machines where various parts (each one usually idealized as a rigid object) are connected to each other with hinges and bearings of one type or another.

The central observation in all rigid-object kinematics is the definition of a rigid object:

All pairs of points on a single rigid object keep constant distance from each other as the object moves.

In this section you will learn how to use rigidity to calculate positions, velocities and accelerations of all points (millions and billions of them) on a rigid object given only a few numbers (9 of them). This goal is achieved by putting together the ideas from Chapter 11 (arbitrary motion of one particle), Chapter 14 (straight-line motion), and Chapter chapter 15 (circular motion of a rigid object in a plane).

Displacement and rotation

When a planar object (say a machine part) $\mathcal{B}$ moves from one configuration in the plane to another it has a displacement and a rotation. It starts in some reference configuration *. We mark a reference point on the body that, in the reference configuration, coincides with a fixed reference point, say O ^①. We also mark a (directed) line on the body that, in the reference configuration, coincides with a fixed reference line, say the positive x axis.

We could measure rotation by measuring the rotation of any line segment connecting any pair of points fixed to the object. For each line we keep track of the angle that line makes with a line fixed in space, say the positive x or y axis. It's simplest to stick to the convention that counter-clockwise rotations are positive (fig. 17.4). The angles $\theta_1, \theta_2, \dots$, all change with time and are all different from each other. But all the angles change the same amount, just like in section 16.1. We can pick any one line we like for definiteness and measure the object rotation by the rotation of that line. So

The net motion of a rigid planar object is described by *translation*, the vector displacement of a reference point from a reference posi-

①The body never has to pass through this reference position, however. For example, the position of an airplane flying from New York to Mumbai is measured relative to a point in the Gulf of Guinea 1000 miles west of Gabon (the location of O° longitude and O° latitude) even though the airplane never goes there (nor does anyone want it to).




Figure 17.4: Rotation of object $\mathcal{B}$ is measured by the rotation of real or imagined lines marked on the object. The lines make different angles: $\theta_1 \neq \theta_2, \theta_2 \neq \theta_3$ etc, but $\dot{\theta}_1 = \dot{\theta}_2 = \dot{\theta}_3 = \dots$. Angular velocity is defined as $\vec{\omega} = \omega \hat{k}$ with $\omega \equiv \dot{\theta}_1 = \dot{\theta}_2 = \dot{\theta}_3 = \dots$.




Figure 17.5: The displacement and rotation of a planar object relative to a reference configuration.

tion $\vec{r}_{o'/o} = \vec{r}_{oo'}$, and a scalar *rotation* θ of the reference line from its reference orientation.

The position of a point on a moving rigid object.

Given that P on the object is at $\vec{r}_{P/0}^*$ in the reference (*) configuration, where is it (What is $\vec{r}_{P/0}$?) after the object has been displaced by $\vec{r}_{o'/o}$ and rotated an angle θ ?

The base-independent or direct vector notation. An easy way to treat this is to write the new position of P as (see fig. 17.5), in the *base-independent* or *direct vector* representation of the position of P,

$$\vec{r}_{P/0} = \vec{r}_{o'/o} + \vec{r}_{P/o'}. \quad (17.1)$$

The vector $\vec{r}_{o'/o}$ describes *translation*, that's half the story. The other term $\vec{r}_{P/o'}$ we find by rotating $\vec{r}_{P/0}^*$ as we did in Section 16.2. This 'base-independent' formula is correct no matter what base vectors are used to represent the vectors in the formula (e.g., $\hat{i}$ and $\hat{j}$ or $\hat{i}'$ and $\hat{j}'$).

Fixed basis or component representation. For a given basis, say $\hat{i}$ and $\hat{j}$ associated with x and y , we can write the coordinates of a point as,

$$\left[\vec{r}_{P/0} \right]_{xy} = \underbrace{\left[\vec{r}_{o'/o} \right]_{xy}}_{\text{displacement}} + \underbrace{[R(\theta)] \left[\vec{r}_{P/o'} \right]_{x'y'}}_{\text{rotation}} \quad (17.2)$$

or, writing out all the components of the vectors and matrices, We get the *fixed basis* or *component* representation of the motion:

$$\begin{bmatrix} x_P \\ y_P \end{bmatrix} = \begin{bmatrix} x_{o'/o} \\ y_{o'/o} \end{bmatrix} + \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x_{P/o'}^* \\ y_{P/o'}^* \end{bmatrix}. \quad (17.3)$$

As the motion progresses the displacement $\begin{bmatrix} x_{o'/o} \\ y_{o'/o} \end{bmatrix}$ changes with time as does the rotation angle θ . In this *fixed basis* or *component* representation of the motion of eqn. (17.3) we get the components of the position in terms of base vectors that are fixed in space.

Example:

If in the reference position a particle on a rigid object is at $\vec{r}_{P/0} = (1\hat{i} + 2\hat{j})$ m and the object displaces by $\vec{r}_{o'/o} = (3\hat{i} + 4\hat{j})$ m and rotates by $\theta = \pi/3$ rad = 60°

relative to that configuration, then its new position is:

$$\begin{aligned}
 [\vec{r}_{P/0}]_{xy} &= [\vec{r}_{0'/0}]_{xy} + [R(\theta)] [\vec{r}_{P/0'}]_{x'y'} \\
 &= \begin{bmatrix} x_{0'/0} \\ y_{0'/0} \end{bmatrix} + \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x_{P/0}^* \\ y_{P/0}^* \end{bmatrix} \\
 &= \left\{ \begin{bmatrix} 3 \\ 4 \end{bmatrix} + \begin{bmatrix} \cos \pi/3 & -\sin \pi/3 \\ \sin \pi/3 & \cos \pi/3 \end{bmatrix} \begin{bmatrix} 1 \\ 2 \end{bmatrix} \right\} \text{ m} \\
 &= \begin{bmatrix} 3.5 - \sqrt{3} \\ 5 + \sqrt{3}/2 \end{bmatrix} \text{ m} \\
 \Rightarrow \vec{r}_{P/0} &= \left((3.5 - \sqrt{3})\hat{i} + (5 + \sqrt{3}/2)\hat{j} \right) \text{ m}
 \end{aligned}$$

Changing-base representation. Finally, the *changing base* representation uses base vectors $\hat{i}', \hat{j}'$ that are aligned with $\hat{i}, \hat{j}$ in the reference configuration but which are glued to the rotating object. If we define x' and y' as the x and y components of P in the reference (*) configuration we have that

$$\begin{aligned}
 [\vec{r}_{P/0}^*]_{xy} &= [\vec{r}_{P/0'}^*]_{x'y'} = \begin{bmatrix} x' \\ y' \end{bmatrix} \\
 \text{so } \vec{r}_{P/0} &= (x_{0'/0}\hat{i} + y_{0'/0}\hat{j}) + (x'\hat{i}' + y'\hat{j}'). \quad (17.4)
 \end{aligned}$$

The second equation above is the *changing base* representation.

Although all three notations are in some sense equivalent, they have their best uses depending on context. The base-independent or direct-vector notation eqn. (17.1) is the most direct, least ornate and shortest to write. The component or fixed base representation eqn. (17.3) is the best for computer calculations. And the changing-base notation eqn. (17.4) is the most explicit for pencil and paper work.

Angular velocity

Because all lines on object $\mathcal{B}$ rotate at the same rate (at a given instant) $\mathcal{B}$'s rotation rate is the single number we call $\omega_{\mathcal{B}}$ ('omega b'). As for the case of pure rotation, we define a vector angular velocity with magnitude $\omega_{\mathcal{B}}$ which is perpendicular to the xy plane:

$$\vec{\omega}_{\mathcal{B}} = \underbrace{\omega_{\mathcal{B}}}_{\dot{\theta}} \hat{k}$$

where $\dot{\theta}$ is the rate of change of the angle of any line marked on object $\mathcal{B}$.

So long as you are careful to define angular velocity by the rotation of line segments and not by the motion of individual particles, the concept of angular velocity in general motion is defined exactly as for an object rotating about a fixed axis. The key kinematic fact is, in words:




Figure 17.6: It is generally best to take positive ω to be counterclockwise when viewed from the positive z axis.

On a rigid object in 2D any given point is moving in circles about any other given point (relative to that point).

So you can think of the general planar motion of a rigid object as the general motion of a point plus uniform circular motion about that point. When a rigid object moves it always has an angular velocity (possibly zero). If we call the object $\mathcal{B}$ (script B for body), we then call the object's angular velocity $\vec{\omega}_{\mathcal{B}}$. Again, it is generally best to use the CCW sign convention that when $\omega_{\mathcal{B}} > 0$ the object is rotating counterclockwise when viewed looking in from a point outside the object on the positive z axis (that is, 'looking down', see fig. 17.6).

The angular velocity vector $\vec{\omega}_{\mathcal{B}}$ of an object $\mathcal{B}$ describes its rate and direction of rotation. For planar motions $\vec{\omega}_{\mathcal{B}} = \omega_{\mathcal{B}} \hat{k}$.

Relative velocity of two points on a rigid object

For any two points A and B glued to a rigid object $\mathcal{B}$ the relative velocity $\vec{v}_{B/A}$ of the points ('the velocity of B relative to A') is given by the cross product of the angular velocity of the object with the relative position of the two points (fig. 17.7):

$$\vec{v}_{B/A} \equiv \vec{v}_B - \vec{v}_A = \vec{\omega}_{\mathcal{B}} \times \vec{r}_{B/A}. \quad (17.5)$$




Figure 17.7: The relative velocity of points A and B is in the xy plane and perpendicular to the line segment AB.

That is, the relative velocity of two points on a rigid object is the same as would be predicted for one of the points if the other were stationary. The derivation of this formula is the same as for planar circular motion.

Note that we use three-dimensional cross products even though we are doing planar 2D kinematics. Generally the plane of motion is the xy plane and $\vec{\omega}$ will be in the z direction. Because $\vec{\omega} \times \vec{r}$ must be perpendicular to $\vec{\omega}$ it is perpendicular to the z axis. So the three-dimensional cross product $\vec{\omega} \times \vec{r}$ gives a vector that is perpendicular to $\vec{r}$ and is in the xy plane.

We can also represent the relative velocity in the changing base notation as

$$\begin{aligned} \vec{v}_{B/A} &= \frac{d}{dt} (x'_{B/A} \hat{i}' + y'_{B/A} \hat{j}') \\ &= x'_{B/A} \frac{d}{dt} \hat{i}' + y'_{B/A} \frac{d}{dt} \hat{j}' \\ &= x'_{B/A} (\vec{\omega}_{\mathcal{B}} \times \hat{i}') + y'_{B/A} (\vec{\omega}_{\mathcal{B}} \times \hat{j}'). \end{aligned}$$

That is, the relative velocity is the same as the relative position, but with the base vectors substituted with their rates of change.

Finally, we can use the fixed-base or component notation for position and differentiate the terms (see box 16.5 on page 773):

$$\begin{aligned}
 [\vec{v}_{B/A}]_{xy} &= \frac{d}{dt} \begin{bmatrix} x_{B/A} \\ y_{B/A} \end{bmatrix} \\
 &= \frac{d}{dt} \left\{ \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x_{B/A}^* \\ y_{B/A}^* \end{bmatrix} \right\} \\
 &= \begin{bmatrix} -\dot{\theta} \sin \theta & -\dot{\theta} \cos \theta \\ \dot{\theta} \cos \theta & -\dot{\theta} \sin \theta \end{bmatrix} \begin{bmatrix} x_{B/A}^* \\ y_{B/A}^* \end{bmatrix} \\
 &= \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix} \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x_{B/A}^* \\ y_{B/A}^* \end{bmatrix}
 \end{aligned}$$

where $x_{B/A}^*$ and $y_{B/A}^*$ are the components of the position of B with respect to A in the reference configuration and hence do not change with time.

Absolute velocity of a point on a rigid object

If one knows the velocity of one point on a rigid object and one also knows the angular velocity of the object, then one can find the velocity of any other point. How? By addition. Say we know the velocity of point A, the angular velocity of the object, and the relative position of A and B, then

$$\begin{aligned}
 \vec{v}_B &= \vec{v}_A + (\vec{v}_B - \vec{v}_A) \\
 &= \vec{v}_A + \vec{v}_{B/A} \\
 &= \vec{v}_A + \underbrace{\vec{\omega}_B \times \vec{r}_{B/A}}_{\vec{r}_B - \vec{r}_A} \quad (17.6)
 \end{aligned}$$

That is, the absolute velocity of the point B is the absolute velocity of the point A plus the velocity of the point B relative to the point A (fig. 17.8).

Equation (17.6) is a 2D vector equation, and thus equivalent to 2 scalar equations, in 4 vectors which have 7 independent components ($\vec{\omega}$ only has one independent component). Generally one could use eqn. (17.6) to solve for any 2 components in terms of the other 5.

Instantaneous Center of Rotation. Interestingly, for any planar object with non-zero ω there is some point C ‘on’ the object that has exactly zero velocity (fig. 17.9). By ‘on’ the object we mean a point that moves with the object in a rigid way. Imagine a giant sheet of clear plexiglass glued to the object and extending way beyond the object. By ‘on’ the object we




Figure 17.8: Absolute velocity of a point on a rigid object: $\vec{v}_B = \vec{v}_A + \omega \times \vec{r}_{B/A}$




Figure 17.9: The center of rotation C is that point ‘on’ the object that has zero velocity. So long as $\omega \neq 0$ there always is such a point.

mean a point on the plexiglass. Why must there be such a point? Consider a point A on the object with some velocity. Relative to A the other points are going in circles. Each radial line extending from A has a relative velocity orthogonal to that line. Thus, considering all radial lines, every velocity direction is represented. And the relative velocities have magnitudes from 0 to infinity as points on a radial line are scanned from A outwards. Thus each possible relative velocity is had by some point ‘on’ the body. And one of those exactly cancels the velocity of A. Thus some point C has no velocity and all other points on the body rotate around it. This point is called the *center of rotation*. For other than purely circular motion, as an object moves, its center of rotation changes with time. See Sample 17.2 on page 850 for more details.

When trying to understand a mechanism it is often useful to think about the locus of locations of the center of rotation of each of the parts.

Angular acceleration

The angular acceleration $\vec{\alpha}$ (‘alpha’) of a rigid object is the rate of change of angular velocity, $\vec{\alpha} = \dot{\vec{\omega}}$. The angular acceleration of a object $\mathcal{B}$ is $\vec{\alpha}_{\mathcal{B}}$. As for angular velocity, in 2D angular acceleration is perpendicular to the plane of motion:

$$\vec{\omega} = \omega \hat{\mathbf{k}} \quad \text{and} \quad \vec{\alpha} = \alpha \hat{\mathbf{k}} = \dot{\omega} \hat{\mathbf{k}}.$$

In 2D the angular acceleration is only due to the speeding up or slowing down of the rotation rate; i.e., $\alpha = \dot{\omega} = \ddot{\theta}$.

Relative acceleration of two points on a rigid object

For any two points A and B glued to a rigid object $\mathcal{B}$, the acceleration of B relative to A is

$$\begin{aligned} \vec{a}_{B/A} &= \frac{d}{dt} \vec{v}_{B/A} \\ &= \frac{d}{dt} \{ \vec{\omega}_{\mathcal{B}} \times \vec{r}_{B/A} \} \\ &= \dot{\vec{\omega}}_{\mathcal{B}} \times \vec{r}_{B/A} + \vec{\omega}_{\mathcal{B}} \times (\vec{v}_{B/A}), \\ &= \dot{\vec{\omega}}_{\mathcal{B}} \times \vec{r}_{B/A} + \vec{\omega}_{\mathcal{B}} \times (\vec{\omega}_{\mathcal{B}} \times \vec{r}_{B/A}), \\ &= \alpha_{\mathcal{B}} \hat{\mathbf{k}} \times \vec{r}_{B/A} + (-\omega_{\mathcal{B}}^2 \vec{r}_{B/A}), \end{aligned} \quad (17.7)$$

This is the base-independent or direct-vector expression for relative acceleration. If point A has no acceleration, this formula for relative acceleration reduces to the total acceleration of a point undergoing circular motion from Chapter 15.

Equation (17.7) could also be derived, with some algebra, by taking two time derivatives of the relative position coordinate expression

$$\left[\vec{r}_{B/A} \right]_{xy} = [R(\theta)] \left[\vec{r}_{B/A}^* \right]_{x'y'},$$

or by taking two time derivatives of the changing base vector expression

$$\bar{\mathbf{r}}_{B/A} = x'_{B/A} \hat{\mathbf{i}}' + y'_{B/A} \hat{\mathbf{j}}'.$$

Absolute acceleration of a point on a rigid object

If one knows the acceleration of one point on a rigid body *and* the angular velocity and acceleration of the body, then one can find the acceleration of any other point. How? Add the absolute acceleration of one point to the acceleration of the second relative to the first.

$$\begin{aligned} \bar{\mathbf{a}}_B &= \bar{\mathbf{a}}_A + (\bar{\mathbf{a}}_B - \bar{\mathbf{a}}_A) = \bar{\mathbf{a}}_A + \bar{\mathbf{a}}_{B/A} \\ &= \bar{\mathbf{a}}_A + \bar{\boldsymbol{\omega}}_B \times (\bar{\boldsymbol{\omega}}_B \times \bar{\mathbf{r}}_{B/A}) + \dot{\bar{\boldsymbol{\omega}}}_B \times \bar{\mathbf{r}}_{B/A} \\ &= \bar{\mathbf{a}}_A - \omega_B^2 \bar{\mathbf{r}}_{B/A} + \alpha_B \hat{\mathbf{k}} \times \bar{\mathbf{r}}_{B/A} \end{aligned} \quad (17.8)$$

This is the base-independent or direct-vector expression for acceleration. The fixed-base (component) and changing-base notations are somewhat more complex.

Equation 17.8 is often called ‘the three term acceleration formula’ because the acceleration of B is the sum of three terms. First is $\bar{\mathbf{a}}_A$, the acceleration of some point A on the object. Second is $\bar{\boldsymbol{\omega}}_B \times (\bar{\boldsymbol{\omega}}_B \times \bar{\mathbf{r}}_{B/A})$, the centripetal acceleration of B going in circles relative to A. It is directed from B towards A. Third is $\dot{\bar{\boldsymbol{\omega}}}_B \times \bar{\mathbf{r}}_{B/A}$, due to the change in the magnitude of the angular velocity. The third term is in the direction normal to the line from A to B (tangent to the circle of B going around A).

Example: Robot arm

Given the configuration shown in fig. 17.10 the acceleration of point B can be found by thinking of link AB as the object $\mathcal{B}$ in eqn. (17.8) and using what you know about circular motion to find the acceleration of A:

$$\begin{aligned} \bar{\mathbf{a}}_B &= \bar{\mathbf{a}}_A - \omega_B^2 \bar{\mathbf{r}}_{B/A} + \alpha_B \hat{\mathbf{k}} \times \bar{\mathbf{r}}_{B/A} \\ &= (-\omega_{OA}^2 \ell \hat{\mathbf{j}} - \dot{\omega}_{OA} \ell \hat{\mathbf{i}}) - (\omega_{AB}^2 \ell \hat{\mathbf{i}}) + (\dot{\omega}_{AB} \hat{\mathbf{k}} \times (\ell \hat{\mathbf{i}})) \\ &= -(\dot{\omega}_{OA} \ell + \omega_{AB}^2 \ell) \hat{\mathbf{i}} + (-\omega_{OA}^2 \ell + \dot{\omega}_{AB} \ell) \hat{\mathbf{j}} \end{aligned}$$

[Note that $\omega_{AB} \neq \dot{\theta}$ where θ is the angle between the links. Rather $\omega_{AB} = \omega_{OA} + \dot{\theta}$.]

Computer graphics

Given one point given by the xy pair $\begin{bmatrix} x_0 \\ y_0 \end{bmatrix}$ we can find out what happens to it by rotation $[R]$ as

$$\begin{bmatrix} x \\ y \end{bmatrix} = [R] \begin{bmatrix} x_0 \\ y_0 \end{bmatrix}.$$




Figure 17.10: A two link robot arm.

For example the point $\begin{bmatrix} 0 \\ 2 \end{bmatrix}$ gets changed by a 45 deg rotation to

$$\begin{bmatrix} x \\ y \end{bmatrix} = [R] \begin{bmatrix} x_0 \\ y_0 \end{bmatrix} = \begin{bmatrix} \cos \frac{\pi}{4} & -\sin \frac{\pi}{4} \\ \sin \frac{\pi}{4} & \cos \frac{\pi}{4} \end{bmatrix} \begin{bmatrix} 0 \\ 2 \end{bmatrix} \\ \approx \begin{bmatrix} .7 & -.7 \\ .7 & .7 \end{bmatrix} \begin{bmatrix} 0 \\ 2 \end{bmatrix} \approx \begin{bmatrix} -1.4 \\ 1.4 \end{bmatrix}.$$

A translation is just a vector addition. For example the point $\begin{bmatrix} -1.4 \\ 1.4 \end{bmatrix}$ gets translated a distance 2 in the y direction by the addition of $\begin{bmatrix} x_t \\ y_t \end{bmatrix} = \begin{bmatrix} 0 \\ 2 \end{bmatrix}$ like this

$$\begin{bmatrix} x \\ y \end{bmatrix}_{\text{translated}} = \begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} x_t \\ y_t \end{bmatrix} = \begin{bmatrix} -1.4 \\ 1.4 \end{bmatrix} + \begin{bmatrix} 0 \\ 2 \end{bmatrix} = \begin{bmatrix} -1.4 \\ 3.4 \end{bmatrix}.$$

Putting these together the point $\begin{bmatrix} x_0 \\ y_0 \end{bmatrix}$ gets rotated and translated by first multiplying by the rotation matrix and then adding the translation:

$$\begin{bmatrix} x \\ y \end{bmatrix} = [R] \begin{bmatrix} x_0 \\ y_0 \end{bmatrix} + \begin{bmatrix} x_t \\ y_t \end{bmatrix} \approx \begin{bmatrix} .7 & -.7 \\ .7 & .7 \end{bmatrix} \begin{bmatrix} 0 \\ 2 \end{bmatrix} + \begin{bmatrix} 0 \\ 2 \end{bmatrix} \approx \begin{bmatrix} -1.4 \\ 3.4 \end{bmatrix}.$$

A collection of points all rotated the same amount and then all translated the same amount keep their relative distances.

A picture is a set of points on a plane. If all the points are rotated and translated the same amount the picture is rotated and translated. Thus a picture of a rigid object described by points is rigidly rotated and translated. On a computer line drawings are often represented as a connect-the-dots picture. The picture is represented by the x and y coordinates of the reference dots at the corners. These can be stored in an array with the first row being the x coordinates and the second row the y coordinates as explained on page 762. Each column of this matrix represents one point of the connect-the-dots picture. Thus a primitive picture of a house at the origin is given by the array

$$[P_0] \equiv [xy \text{ points originally}] = \begin{bmatrix} 0 & 2 & 2 & 1 & 0 & 0 \\ 0 & 0 & 2 & 3 & 2 & 1 \end{bmatrix}$$

with the lower left corner of the house at the origin.

To rotate this picture we rotate each of the columns of the matrix P_0 . But this is exactly what is accomplished by the matrix multiplication $[R][P_0]$. To translate the points you add the translation vector to each of the columns of the resulting matrix. Thus the whole picture rotated by 45° and translated up by 1 is given by




Figure 17.11: (a) A house drawn as 6 dots connected by line segments. The first and last point are the same. (b) The same house but rigidly rotated and translated.

$$[P_{\text{new}}] = [R][P_0] + \begin{bmatrix} x_t \\ y_t \end{bmatrix} \approx \begin{bmatrix} .7 & -.7 \\ .7 & .7 \end{bmatrix} [P_0] + \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

which gives a new array of points that, when connected give the picture shown. We have allowed the informal notation of adding a column matrix to a rectangular matrix, by which we mean adding to each column of the rectangular matrix.

To animate the motion of a house flying in, say, the Wizard of Oz, you would first define the house as the set of points $[P_0]$. Then define, maybe by means of numerical solution of differential equations, a set of rotations and translations. Then for each rotation and translation the picture of the house should be drawn, one after the other. The sequence of such pictures is an animation of a flying and spinning house.

Summary of the kinematics of one rigid object in general 2D motion

You can use the position of one reference point and the rotation of the object as simple kinematic measures of the entire motion of the object. If you know the position, velocity, and acceleration of one point on a rigid object (represented by 6 scalars, say), and you know the angular rate and angular acceleration (3 scalars) then you can find the position, velocity and acceleration of any point on the object (also given its initial position). In 2D, just 9 numbers tell you the position, velocity, and acceleration of any of the billions of points whose initial positions you know^②.

②In 1D it takes just 3 numbers and in 3D just 18. The unusual pattern (3,9,18) comes from rotation being characterized by 0, 1, and 3 numbers in 1, 2, and 3 dimensions, respectively.

SAMPLE 17.1 Velocity of a point on a rigid body in planar motion.

An equilateral triangular plate ABC is in motion in the x - y plane. At the instant shown in the figure, point B has velocity $\vec{v}_B = 0.3 \text{ m/s} \hat{i} + 0.6 \text{ m/s} \hat{j}$ and the plate has angular velocity $\vec{\omega} = 2 \text{ rad/s} \hat{k}$.

1. Find the velocity of point A using vector calculations.
2. Find the velocity of point C using matrix calculations.

Solution

1. We are given $\vec{v}_B$ and ω , and we need to find $\vec{v}_A$, the velocity of point A on the same rigid body. We know that,

$$\vec{v}_A = \vec{v}_B + \vec{\omega} \times \vec{r}_{A/B}$$

Thus, to find $\vec{v}_A$, we need to find $\vec{r}_{A/B}$. Let us take an x - y coordinate system whose origin coincides with point A of the plate at the instant of interest and the x -axis is along AB. Then,

$$\vec{r}_{A/B} = \vec{r}_A - \vec{r}_B = \vec{0} - (0.2 \text{ m} \hat{i}) = -0.2 \text{ m} \hat{i}$$

Thus,

$$\begin{aligned} \vec{v}_A &= \vec{v}_B + \vec{\omega} \times \vec{r}_{A/B} \\ &= (0.3 \hat{i} + 0.6 \hat{j}) \text{ m/s} + 2 \text{ rad/s} \hat{k} \times (-0.2 \hat{i}) \text{ m} \\ &= (0.3 \hat{i} + 0.2 \hat{j}) \text{ m/s}. \end{aligned}$$

$$\vec{v}_A = (0.3 \hat{i} + 0.2 \hat{j}) \text{ m/s}$$

2. Let xy axes with origin at A be fixed in space with x -axis along AB at the instant of interest. Let $x'y'$ axes be fixed to the plate with origin at O and the x' -axis along AC as shown in fig. 17.13. Thus the coordinates of point C in the rotating axes are

$$\begin{bmatrix} x'_C \\ y'_C \end{bmatrix} = \begin{bmatrix} 0.2 \text{ m} \\ 0 \end{bmatrix}$$

Clearly, at the instant of interest, the rotating axes make an angle of $\theta = \pi/3$ with the fixed axes. Now, we can calculate the velocity of point C as follows.

$$[\vec{v}_C]_{xy} = [\vec{v}_A]_{xy} + \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix} \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x'_{C/A} \\ y'_{C/A} \end{bmatrix}.$$

Using $\theta = \pi/3$, the angle that the rotating axes make with the fixed axes at the instant of interest, and $\omega = 2 \text{ rad/s}$, we get

$$\begin{aligned} [\vec{v}_C]_{xy} &= \begin{bmatrix} 0.3 \text{ m/s} \\ 0.2 \text{ m/s} \end{bmatrix} + \begin{bmatrix} 0 & -2 \text{ rad/s} \\ 2 \text{ rad/s} & 0 \end{bmatrix} \begin{bmatrix} \frac{1}{2} & -\frac{\sqrt{3}}{2} \\ \frac{\sqrt{3}}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} 0.2 \text{ m} \\ 0 \end{bmatrix} \\ &= \begin{bmatrix} 0.3 \text{ m/s} \\ 0.2 \text{ m/s} \end{bmatrix} + \begin{bmatrix} -0.35 \text{ m/s} \\ 0.2 \text{ m/s} \end{bmatrix} = \begin{bmatrix} -0.05 \text{ m/s} \\ 0.4 \text{ m/s} \end{bmatrix}. \end{aligned}$$

Thus, $\vec{v}_C = -0.05 \text{ m/s} \hat{i} + 0.4 \text{ m/s} \hat{j}$. We can also verify this answer by computing $\vec{v}_C = \vec{v}_B + \vec{\omega} \times \vec{r}_{C/B}$.

$$\vec{v}_C = -0.05 \text{ m/s} \hat{i} + 0.4 \text{ m/s} \hat{j}$$




Figure 17.12: The rigid triangular plate ABC rotates counterclockwise at 5 rad/s. Velocity of point B is given. We have to find the velocity of points A and C.




Figure 17.13: Velocity of point A is known. The axes xy are fixed in space and the axes $x'y'$ are fixed to the rotating plate in the orientation shown. Thus in the $x'y'$ axes, the coordinates of point C will always be $x'_C = 0.2 \text{ m}$, $y'_C = 0$.

SAMPLE 17.2 The instantaneous center of rotation. A rigid body is in planar motion. At some instant t , the angular velocity of the body is $\bar{\omega} = 5 \text{ rad/s} \hat{k}$ and the linear velocity of a point C on the body is $\bar{v}_C = 2 \text{ m/s} \hat{i} - 5 \text{ m/s} \hat{j}$. Find the instantaneous center of rotation.

Solution Let a point O be the instantaneous center of rotation. We need to find the location of O using the given information. Whether O lies inside the object or outside is irrelevant here since the object boundary is not specified. So, let us consider an abstract rigid object as shown in fig. 17.14. What we know about O is that it has zero velocity (since it is the center of rotation). Let point O be a distance r away from C in some unknown direction $\hat{n}$ (to be found). Thus, $\bar{r}_{O/C} = r\hat{n}$ is the position vector of point O with respect to point C. Now,




Figure 17.14

$$\begin{aligned}\bar{v}_C &= \underbrace{\bar{v}_O}_{\bar{0}} + \bar{\omega} \times \underbrace{\bar{r}_{C/O}}_{-\bar{r}_{O/C}} \\ &= -\omega \hat{k} \times r \hat{n} = -\omega r (\hat{k} \times \hat{n}).\end{aligned}$$

Thus, $\hat{k} \times \hat{n}$ must be parallel to and in the opposite direction of $\bar{v}_C$. Let $\bar{v}_C = v_C \hat{\lambda}$. Then, we must have $\hat{k} \times \hat{n} = -\hat{\lambda}$, which says that $\hat{n}$ must be normal to $\hat{\lambda}$. Since $\hat{\lambda} = \bar{r}_C / |\bar{r}_C| = (2 \text{ m/s} \hat{i} - 5 \text{ m/s} \hat{j}) / (\sqrt{2^2 + 5^2} \text{ m/s}) = 0.37\hat{i} - 0.93\hat{j}$, we can immediately write $\hat{n} = 0.93\hat{i} + 0.37\hat{j}$. So, now,

$$\begin{aligned}v_C \hat{\lambda} &= -\omega r \overbrace{(\hat{k} \times \hat{n})}^{-\hat{\lambda}} \\ \Rightarrow v_C &= \omega r \\ \Rightarrow r &= v_C / \omega \\ &= \sqrt{29} \text{ m/s} / (5 \text{ rad/s}) = 1.08 \text{ m}.\end{aligned}$$

Thus

$$\bar{r}_{O/C} = r\hat{n} = 1.08 \text{ m}(0.93\hat{i} + 0.37\hat{j}) = 1 \text{ m} \hat{i} + 0.4 \text{ m} \hat{j}.$$

$$\bar{r}_{O/C} = 1 \text{ m} \hat{i} + 0.4 \text{ m} \hat{j}$$

Alternatively,

We can find $\bar{r}_{O/C}$ purely by vector algebra. Let $\bar{r}_{O/C} = (x\hat{i} + y\hat{j}) \text{ m}$. So,

$$\begin{aligned}\bar{v}_O &= \bar{v}_C + \bar{\omega} \times \bar{r}_{O/C} \\ \text{or } \bar{0} &= 2 \text{ m/s} \hat{i} - 5 \text{ m/s} \hat{j} + (5 \text{ rad/s}) \hat{k} \times (x\hat{i} + y\hat{j}) \text{ m} \\ &= (2 - 5y) \text{ m/s} \hat{i} + (-5 + 5x) \text{ m/s} \hat{j}.\end{aligned}$$

Dotting this equation with $\hat{i}$ and $\hat{j}$ respectively, we get

$$\begin{aligned}2 - 5y &= 0 \\ -5 + 5x &= 0.\end{aligned}$$

Solving these two equations simultaneously, we get, $x = 1$ and $y = 0.4$. Thus,

$$\bar{r}_{O/C} = 1 \text{ m} \hat{i} + 0.4 \text{ m} \hat{j}$$

as obtained above.

SAMPLE 17.3 A cheerleader throws her baton up in the air in the vertical xy -plane. At an instant when the baton axis is at $\theta = 60^\circ$ from the horizontal, the velocity of end A of the baton is $\vec{v}_A = 2 \text{ m/s} \hat{i} + \sqrt{3} \text{ m/s} \hat{j}$. At the same instant, end B of the baton has velocity in the negative x -direction (but $|\vec{v}_B|$ is not known). If the length of the baton is $\ell = \frac{1}{2} \text{ m}$ and the center-of-mass is in the middle of the baton, find the velocity of the center-of-mass.

Solution

$$\begin{aligned} \text{We are given: } \vec{v}_A &= (2\hat{i} + \sqrt{3}\hat{j}) \text{ m/s} \\ \text{and } \vec{v}_B &= -v_B \hat{i} \end{aligned}$$

where $v_B = |\vec{v}_B|$ is unknown. We need to find $\vec{v}_G$. Using the relative velocity formula for two points on a rigid body, we can write:

$$\vec{v}_G = \vec{v}_A + \vec{\omega} \times \vec{r}_{G/A} \quad (17.9)$$

Here, $\vec{v}_A$ and $\vec{r}_{G/A}$ are known. Thus, to find $\vec{v}_G$, we need to find $\vec{\omega}$, the angular velocity of the baton. Since the motion is in the vertical xy -plane, let $\vec{\omega} = \omega \hat{k}$. Then,

$$\begin{aligned} \vec{v}_B &= \vec{v}_A + \vec{\omega} \times \vec{r}_{B/A} = \vec{v}_A + \omega \hat{k} \times \ell (\cos \theta \hat{i} - \sin \theta \hat{j}) \\ \text{or } -v_B \hat{i} &= (2\hat{i} + \sqrt{3}\hat{j}) \text{ m/s} + \omega \ell (\cos \theta \hat{j} + \sin \theta \hat{i}) \\ &= (2\hat{i} + \sqrt{3}\hat{j}) \text{ m/s} + \omega \cdot \frac{1}{2} \text{ m} \cdot \left(\frac{1}{2} \hat{j} + \frac{\sqrt{3}}{2} \hat{i} \right) \end{aligned}$$

Dotting both sides of this equation with $\hat{j}$ we get:

$$\begin{aligned} 0 &= \sqrt{3} \text{ m/s} + \frac{\omega}{2} \text{ m} \cdot \frac{1}{2} \\ \Rightarrow \omega &= -\sqrt{3} \frac{\text{m}}{\text{s}} \cdot \frac{4}{1 \text{ m}} = -4\sqrt{3} \text{ rad/s.} \end{aligned}$$

Now substituting the appropriate values in Eqn (17.9) we get:

$$\begin{aligned} \vec{v}_G &= \vec{v}_A + \omega \hat{k} \times \frac{\ell}{2} (\cos \theta \hat{i} - \sin \theta \hat{j}) \\ &= \vec{v}_A + \frac{\omega \ell}{2} (\cos \theta \hat{j} + \sin \theta \hat{i}) \\ &= (2\hat{i} + \sqrt{3}\hat{j}) \text{ m/s} - \sqrt{3} \text{ m/s} \cdot \left(\frac{1}{2} \hat{j} + \frac{\sqrt{3}}{2} \hat{i} \right) \\ &= \left(2 - \frac{3}{2} \right) \text{ m/s} \hat{i} + \left(\sqrt{3} - \frac{\sqrt{3}}{2} \right) \text{ m/s} \hat{j} \\ &= \frac{1}{2} \text{ m/s} \hat{i} + \frac{\sqrt{3}}{2} \text{ m/s} \hat{j} \end{aligned}$$

$$\vec{v}_G = (0.5\hat{i} + 0.87\hat{j}) \text{ m/s}$$




Figure 17.15




Figure 17.16




Figure 17.17




Figure 17.18: A board in the back of an accelerating truck.

SAMPLE 17.4 A board in the back of an accelerating truck. A 10 ft long uniform board AB rests in the back of a flat-bed truck as shown in Fig. 17.18. End A of the board is hinged to the bed of the truck. The truck is going on a level road at 55 mph. In preparation for overtaking a vehicle in the front, the trucker accelerates at a rate of 3 mph/s. At the instant when the speed of the truck is 60 mph, the magnitude of the relative velocity and relative acceleration of end B with respect to the bed of the truck are 10 ft/s and 12 ft/s², respectively. There is wind and at this instant, the board has lost contact with point C. If the angle θ between the board and the bed is 45° at the instant mentioned, find

1. the angular velocity and angular acceleration of the board,
2. the absolute velocity and absolute acceleration of point B, and
3. the acceleration of the center-of-mass G of the board.

Solution At the instant of interest, the quantities given are:

$$\begin{aligned}\vec{v}_A &= \text{velocity of the truck} = 60 \text{ mph } \hat{i} = 88 \text{ ft/s } \hat{i} \\ \vec{a}_A &= \text{acceleration of the truck} = 3 \text{ mph/s} = 4.4 \text{ ft/s}^2 \hat{i} \\ |\vec{v}_{B/A}| &= v_{B/A} = \text{magnitude of relative velocity of B} = 10 \text{ ft/s} \\ |\vec{a}_{B/A}| &= a_{B/A} = \text{magnitude of relative acceleration of B} = 12 \text{ ft/s}^2.\end{aligned}$$

Let $\vec{\omega} = \omega \hat{k}$ be the angular velocity and $\vec{\dot{\omega}} = \dot{\omega} \hat{k}$ be the angular acceleration of the board.

1. The relative velocity of end B of the board with respect to end A is

$$\begin{aligned}\vec{v}_{B/A} &= \vec{\omega} \times \vec{r}_{B/A} = \omega \hat{k} \times \ell (\cos \theta \hat{i} + \sin \theta \hat{j}) \\ &= \omega \ell (\cos \theta \hat{j} - \sin \theta \hat{i}) \\ \Rightarrow \omega &= \frac{|\vec{v}_{B/A}|}{\ell} = \frac{v_{B/A}}{\ell} = \frac{10 \text{ ft/s}}{10 \text{ ft}} = 1 \text{ rad/s}.\end{aligned}$$

Note that we have taken the positive value for ω because the board is rotating counterclockwise at the instant of interest (since it is given that the board has lost contact with point C).

Similarly, we can compute the angular acceleration:

$$\begin{aligned}\vec{a}_{B/A} &= \vec{\dot{\omega}} \times \vec{r}_{B/A} - \omega^2 \vec{r}_{B/A} \\ &= \dot{\omega} \hat{k} \times \ell (\cos \theta \hat{i} + \sin \theta \hat{j}) - \omega^2 \ell (\cos \theta \hat{i} + \sin \theta \hat{j}) \\ &= \dot{\omega} \ell (\cos \theta \hat{j} - \sin \theta \hat{i}) - \omega^2 \ell (\cos \theta \hat{i} + \sin \theta \hat{j}) \\ \Rightarrow |\vec{a}_{B/A}| &= \sqrt{(\dot{\omega} \ell)^2 + (\omega^2 \ell)^2} = a_{B/A} \text{ (given)} \\ \Rightarrow a_{B/A}^2 &= (\dot{\omega} \ell)^2 + (\omega^2 \ell)^2 \\ \Rightarrow \dot{\omega} &= \sqrt{\frac{a_{B/A}^2}{\ell^2} - \omega^4} = \sqrt{\left(\frac{12 \text{ ft/s}^2}{10 \text{ ft}}\right)^2 - (1 \text{ rad/s})^4} \\ &= \pm 0.663 \text{ rad/s}^2.\end{aligned}$$

Once again, we select the positive value for $\dot{\omega}$ since we assume that the board accelerates counterclockwise.

$$\vec{\omega} = 1 \text{ rad/s } \hat{k}, \quad \vec{\dot{\omega}} = 0.663 \text{ rad/s}^2 \hat{k}$$

2. The absolute velocity and the absolute acceleration of the end point B can be found as follows.

$$\begin{aligned}
 \vec{v}_B &= \vec{v}_A + \vec{v}_{B/A} \\
 &= v_A \mathbf{i} + v_{B/A}(\cos \theta \mathbf{j} - \sin \theta \mathbf{i}) \\
 &= 88 \text{ ft/s} \mathbf{i} + 10 \text{ ft/s} \left(\frac{1}{\sqrt{2}} \mathbf{j} - \frac{1}{\sqrt{2}} \mathbf{i} \right) \\
 &= 80.93 \text{ ft/s} \mathbf{i} + 7.07 \text{ ft/s} \mathbf{j}.
 \end{aligned}$$

$$\begin{aligned}
 \vec{a}_B &= \vec{a}_A + \vec{a}_{B/A} \\
 &= \vec{a}_A + \dot{\vec{\omega}} \times \vec{r}_{B/A} - \omega^2 \vec{r}_{B/A} \\
 &= a_A \mathbf{i} + \dot{\omega} \mathbf{k} \times \ell(\cos \theta \mathbf{i} + \sin \theta \mathbf{j}) - \omega^2 \ell(\cos \theta \mathbf{i} + \sin \theta \mathbf{j}) \\
 &= (a_A - \dot{\omega} \ell \sin \theta - \omega^2 \ell \cos \theta) \mathbf{i} + (\dot{\omega} \ell \cos \theta - \omega^2 \ell \sin \theta) \mathbf{j} \\
 &= \left(4.4 \text{ ft/s}^2 - \frac{0.66}{\text{s}^2} \cdot 10 \text{ ft} \cdot \frac{1}{\sqrt{2}} - \frac{1}{\text{s}^2} \cdot 10 \text{ ft} \cdot \frac{1}{\sqrt{2}} \right) \mathbf{i} \\
 &\quad + \left(\frac{0.66}{\text{s}^2} \cdot 10 \text{ ft} \cdot \frac{1}{\sqrt{2}} - \frac{1}{\text{s}^2} \cdot 10 \text{ ft} \cdot \frac{1}{\sqrt{2}} \right) \mathbf{j} \\
 &= -7.34 \text{ ft/s}^2 \mathbf{i} - 2.40 \text{ ft/s}^2 \mathbf{j}.
 \end{aligned}$$

$$\vec{v}_B = (80.93 \mathbf{i} + 7.07 \mathbf{j}) \text{ ft/s}, \quad \vec{a}_B = -(7.34 \mathbf{i} + 2.40 \mathbf{j}) \text{ ft/s}^2.$$

3. Now, we can easily calculate the acceleration of the center-of-mass as follows.

$$\begin{aligned}
 \vec{a}_G &= \vec{a}_A + \vec{a}_{G/A} \\
 &= a_A \mathbf{i} + \dot{\vec{\omega}} \times \vec{r}_{G/A} - \omega^2 \vec{r}_{G/A} \\
 &= a_A \mathbf{i} + \dot{\omega} \mathbf{k} \times \frac{\ell}{2}(\cos \theta \mathbf{i} + \sin \theta \mathbf{j}) - \omega^2 \frac{\ell}{2}(\cos \theta \mathbf{i} + \sin \theta \mathbf{j}) \\
 &= a_A \mathbf{i} + \dot{\omega} \frac{\ell}{2}(\cos \theta \mathbf{j} - \sin \theta \mathbf{i}) - \omega^2 \frac{\ell}{2}(\cos \theta \mathbf{i} + \sin \theta \mathbf{j}) \\
 &= 4.4 \text{ ft/s}^2 \mathbf{i} + 0.663 \text{ rad/s}^2 \cdot \frac{10 \text{ ft}}{2} \cdot \left(\frac{1}{\sqrt{2}} \mathbf{j} - \frac{1}{\sqrt{2}} \mathbf{i} \right) \\
 &\quad - (1 \text{ rad/s})^2 \cdot \frac{10 \text{ ft}}{2} \cdot \left(\frac{1}{\sqrt{2}} \mathbf{i} + \frac{1}{\sqrt{2}} \mathbf{j} \right) \\
 &= -1.48 \text{ ft/s}^2 \mathbf{i} - 1.19 \text{ ft/s}^2 \mathbf{j}.
 \end{aligned}$$

$$\vec{a}_G = -(1.48 \mathbf{i} + 1.19 \mathbf{j}) \text{ ft/s}^2$$

Comments: This problem is admittedly artificial. We, however, solve this problem to show kinematic calculations.




Figure 17.19

SAMPLE 17.5 Tracking motion. A cart moves along a suspended curved path. A rod AB of length $\ell = 1$ m hangs from the cart. End A of the rod is attached to a motor on the cart. The other end, B, hangs freely. The motor rotates the rod such that $\theta(t) = \theta_0 \sin(\lambda t)$ (θ is measured with respect to a fixed vertical line) while the cart moves along the path such that $\vec{r}_A = t\hat{i} + \frac{t^3}{18}\hat{j}$, where all variables (r, t , etc.) are nondimensional.

1. Find the velocity and acceleration of point B as a function of nondimensional time t .
2. Take $\theta_0 = \pi/3$ and $\lambda = 6$. Find and plot the position of the bar at $t = 0, 0.1, 0.3, 0.9, 1, 1.1, 1.2$, and 1.5 . Find and draw $\vec{v}_B$ and $\vec{a}_B$ at the specified t .

Solution

1. The velocity and acceleration of point B are given by

$$\vec{v}_B = \vec{v}_A + \vec{v}_{B/A} = \vec{v}_A + \vec{\omega} \times \vec{r}_{B/A}$$

$$\vec{a}_B = \vec{a}_A + \dot{\vec{\omega}} \times \vec{r}_{B/A} - \omega^2 \vec{r}_{B/A}.$$

Thus, in order to find the velocity and acceleration of point B, we need to find the velocity and acceleration of point A and the angular velocity and angular acceleration of the bar. We are given the position of point A and the angular position of the bar as functions of t . We can, therefore, find $\vec{v}_A$, $\vec{a}_A$, $\vec{\omega}$, and $\dot{\vec{\omega}}$ by differentiating the given functions with respect to t .

$$\vec{r}_A = t\hat{i} + \frac{t^3}{18}\hat{j}$$

$$\Rightarrow \vec{v}_A \equiv \dot{\vec{r}}_A = \hat{i} + (t^2/6)\hat{j} \quad (17.10)$$

$$\Rightarrow \vec{a}_A \equiv \dot{\vec{v}}_A = (t/3)\hat{j} \quad (17.11)$$

and

$$\theta\hat{k} = \theta_0 \sin(\lambda t)\hat{k}$$

$$\Rightarrow \vec{\omega} \equiv \dot{\theta}\hat{k} = \theta_0\lambda \cos(\lambda t)\hat{k} \quad (17.12)$$

$$\Rightarrow \dot{\vec{\omega}} \equiv \ddot{\theta}\hat{k} = -\theta_0\lambda^2 \sin(\lambda t)\hat{k}. \quad (17.13)$$

So,

$$\begin{aligned} \vec{v}_B &= \vec{v}_A + \vec{\omega} \times \ell(\sin\theta\hat{i} - \cos\theta\hat{j}) \\ &= \hat{i} + (t^2/6)\hat{j} + \ell\dot{\theta}(\sin\theta\hat{j} + \cos\theta\hat{i}) \\ &= (1 + \ell\dot{\theta}\cos\theta)\hat{i} + (t^2/6 + \ell\dot{\theta}\sin\theta)\hat{j} \end{aligned} \quad (17.14)$$

$$\begin{aligned} \vec{a}_B &= \vec{a}_A + \ddot{\theta}\hat{k} \times \ell(\sin\theta\hat{i} - \cos\theta\hat{j}) - \dot{\theta}^2\ell(\sin\theta\hat{i} - \cos\theta\hat{j}) \\ &= (t/3)\hat{j} + \ell\ddot{\theta}\sin\theta\hat{j} + \ell\ddot{\theta}\cos\theta\hat{i} - \ell\dot{\theta}^2\sin\theta\hat{i} + \ell\dot{\theta}^2\cos\theta\hat{j} \\ &= \ell(\ddot{\theta}\cos\theta - \dot{\theta}^2\sin\theta)\hat{i} + [t/3 + \ell(\ddot{\theta}\sin\theta + \dot{\theta}^2\cos\theta)]\hat{j} \end{aligned} \quad (17.15)$$

where $\theta = \theta_0 \sin(\lambda t)$, $\dot{\theta} = \theta_0\lambda \cos(\lambda t)$, and $\ddot{\theta} = -\theta_0\lambda^2 \sin(\lambda t) = -\lambda^2\theta$. Thus $\vec{v}_B$ and $\vec{a}_B$ are functions of t .

2. The position of the rod at any time t is specified by the position of the two end points A and B (or alternatively, the position of A and the angle of the rod θ). The

position of point A is easily determined by substituting the value of t in the given expression for $\vec{r}_A$. The position of end B is given by

$$\begin{aligned}\vec{r}_B &= \vec{r}_A + \vec{r}_{B/A} = t\hat{i} + (t^3/18)\hat{j} + \ell(\sin\theta\hat{i} - \cos\theta\hat{j}) \\ &= (t + \ell \sin\theta)\hat{i} + (t^3/18 - \ell \cos\theta)\hat{j}.\end{aligned}$$

To compute the positions, velocities, and accelerations of end points A and B at the given instants, we first compute θ , $\dot{\theta}$, and $\ddot{\theta}$, and then substitute them in the expressions for $\vec{r}_A$, $\vec{r}_B$, $\vec{v}_A$, $\vec{v}_B$, $\vec{a}_A$, and $\vec{a}_B$. A pseudocode for computer calculation is given below.

```
t = [0 0.1 0.3 0.9 1.0 1.1 1.2 1.5]
theta0=pi/3, L=.5, lam=6
for each t, compute
    theta = theta0*sin(lam*t)
    w = lam*theta0*cos(lam*t)
    wdot = -lam^2*theta
    % Position of A and B
    xA=t, yA=t^3/18
    xB = xA + L*sin(theta)
    yB = yA - L*cos(theta)
    % Velocity of A and B
    uA = 1, vA = t^2/6
    uB = uA + L*w.*cos(theta)
    vB = vA + L*w.*sin(theta)
    % Acceleration of A and B
    axA = 0, ayA = t/3
    axB = L*wdot*cos(theta) - L*w^2*sin(theta)
    ayB = ayA + L*wdot*sin(theta) + L*w^2*cos(theta)
```

From the above calculation, we get the desired quantities at each t . For example, at $t = 0$ we get,

$$\begin{aligned}x_A = 0, y_A = 0, x_B = 0, y_B = -0.5 \\ u_A = 1, v_A = 0, u_B = 4.14, v_B = 0, ax_B = 0, ay_B = 19.74\end{aligned}$$

which means,

$$\vec{r}_A = \vec{0}, \quad \vec{r}_B = -0.5\hat{j}, \quad \vec{v}_A = \hat{i}, \quad \vec{v}_B = 4.14\hat{i}, \quad \vec{a}_B = 19.74\hat{j}.$$

The position of the bar, the velocity vectors at points A and B, and the acceleration vector at B, thus obtained, are shown in fig. 17.20 graphically. ①




Figure 17.20: Position, velocity of the end points A and B, and acceleration of point B at various time instants.

① We can take several values of t , say 400 equally spaced values between $t = 0$ and $t = 4$, and draw the bar at each t to see its motion and the trajectory of its end points. fig. 17.21 shows such a graph.





Figure 17.21: Graph of closely spaced configuration of the bar between $t = 0$ to $t = 4$.

17.1 Rigid object kinematics

Preparatory Problems

17.1.1 A disk of radius R is hinged at point O at the edge of the disk, approximately as shown. It rotates counterclockwise with angular velocity $\dot{\theta} = \bar{\omega}$. A bolt is fixed on the disk at point P at a distance r from the center of the disk. A frame $x'y'$ is fixed to the disk with its origin at the center C of the disk. The bolt position P makes an angle ϕ with the x' -axis. At the instant of interest, the disk has rotated by an angle θ .

- Write the position vector of point P relative to C in the $x'y'$ coordinates in terms of given quantities.
- Write the position vector of point P relative to O in the xy coordinates in terms of given quantities.
- Write the expressions for the rotation matrix $R(\theta)$ and the angular velocity matrix $S(\bar{\omega})$.
- Find the velocity of point P relative to C using $R(\theta)$ and the angular velocity matrix $S(\bar{\omega})$.
- Using $R = 30$ cm, $r = 25$ cm, $\theta = 60^\circ$, and $\phi = 45^\circ$, find $[\bar{r}_{C/O}]_{xy}$, and $[\bar{v}_{P/O}]_{xy}$ at the instant shown.
- Assuming that the angular speed is $\omega = 10$ rad/s at the instant shown, find $[\bar{v}_{C/O}]_{xy}$ and $[\bar{v}_{P/O}]_{xy}$ taking other quantities as specified above.




Problem 17.1.1

17.1.2 A uniform rigid rod AB of length $\ell = 1$ m rotates at a constant angular speed ω about an unknown fixed point. At the instant shown, the velocities of the two ends of the rod are $\bar{v}_A = -1$ m/s $\hat{i}$ and $\bar{v}_B = 1$ m/s $\hat{j}$.

- Find the angular velocity of the rod.


- Find the center of rotation of the rod.



Problem 17.1.2

17.1.3 A square plate $ABCD$ rotates at a constant angular speed about an unknown point in its plane. At the instant shown, the velocities of the two corner points A and D are $\bar{v}_A = -2$ ft/s $(\hat{i} + \hat{j})$ and $\bar{v}_D = -(2$ ft/s) $\hat{i}$, respectively.

- Find the center of rotation of the plate.
- Find the acceleration of the center of mass of the plate.




Problem 17.1.3

More-Involved Problems

17.1.4 A ten foot ladder is leaning between a floor and a wall. The top of the ladder is sliding down the wall at one foot per second. (The foot is simultaneously sliding out on the floor). When the ladder makes a 45 degree angle with the vertical what is the speed of the midpoint of the ladder?

17.1.5 The slender rod AB rests against the step of height h , while end “A” is


moved along the ground at a constant velocity v_o . Find $\dot{\phi}$ and $\ddot{\phi}$ in terms of x , h , and v_o . Is $\dot{\phi}$ positive or negative? Is $\ddot{\phi}$ positive or negative?



Problem 17.1.5

17.1.6 Consider the motion of a rigid ladder which can slide on a wall and on the floor as shown in the figure. The point A on the ladder moves parallel to the wall. The point B moves parallel to the floor. Yet, at a given instant, both have velocities that are consistent with the ladder rotating about some special point, the center of rotation (COR). Define appropriate dimensions for the problem.

- Find the COR for the ladder when it is at some given position (and moving, of course). [Hint: if a point A is ‘going in circles’ about another point C , that other point C must be in the direction perpendicular to the motion of A .]
- As the ladder moves, the COR changes with time. What is the set of points on the plane that are the COR’s for the ladder as it falls from straight up to lying on the floor?




Problem 17.1.6

17.1.7 A car driver on a very boring highway is carefully monitoring her speed. Over a one hour period, the car travels on a curve with constant radius of curvature, $\rho = 25$ mi, and its speed increases uniformly from 50 mph to 60 mph. What

is the acceleration of the car half-way through this one hour period, in path coordinates?

17.1.8 The bar AB shown in the figure is 1 m long. The end A of the bar is dragged to the left on the horizontal floor at a constant speed $v_0 = 0.2$ m/s. The other end of the bar drags along the inclined plane that makes an angle $\phi = 60^\circ$ with the horizontal.


- Does the end B of the rod also have a constant speed? Does it imply that the rod has a constant angular velocity? Guess your answer and write down your reasoning. No calculations.
- Find an expression for the angular velocity of the rod in terms of θ , ϕ , ℓ , and v_0 .*
- Find the velocity of end B when $\theta = 30^\circ$.



Problem 17.1.8


17.1.9 The disk shown in the figure drives the slider AB. The disk rotates clockwise at a constant angular speed $\omega_D = 60$ rpm. The radius of the disk is $R = 0.25$ m.

- Find the velocity of collar A when $\theta = 30^\circ$.
- Find the acceleration of collar A when $\theta = 30^\circ$.
- Find the maximum and minimum velocity of the collar and the corresponding angle θ of the slider.



Problem 17.1.9


17.1.10 A rod AC of length $\ell = 2$ m is mounted on a cart at point C. The cart slides down under gravity on a frictionless surface inclined at $\phi = 45^\circ$ from the horizontal. Assume that bar has negligible mass compared to that of the cart. The cart is released from rest and it reaches the position shown in $t = 2$ s. At the instant shown, $\theta = 60^\circ$, and rod AC has an angular velocity $\vec{\omega} = 0.5$ rad/s $\hat{k}$ and angular acceleration $\vec{\alpha} = 1$ rad/s² $\hat{k}$. Find the velocity and acceleration of the center of mass of the rod at the instant shown.



Problem 17.1.10

17.1.11 A vertical bar pendulum AB of length $\ell = 4$ ft is mounted on a cart at point A. The cart has a motor that drives the bar pendulum back and forth about the vertical position such that $\theta(t) = \theta_0 \sin \omega t$ where $\theta_0 = \pi/6$ and $\omega = \pi$ rad/s. The cart moves at a constant speed $v_0 = 2$ ft/s on a sinusoidal track represented by $y(x) = y_0 \sin \lambda x$ where $y_0 = 0.5$ ft and $\lambda = \pi/4$ ft.

- Find the velocity of point B when $\theta = 0$.
- Find and plot the position of point B for one full oscillation of the bar, assuming the bar starts from its leftmost angular position (that is, $\theta = -\theta_0$) when the cart is on one of the crests of the track.




Problem 17.1.11

17.1.12 The center of mass of a javelin travels on a more or less parabolic path while the javelin rotates during its flight. In a particular throw, the velocity of the center of mass of a javelin is measured to

be $\vec{v}_C = 10$ m/s $\hat{i}$ when the center of mass is at its highest point $h = 6$ m. As the javelin lands on the ground, its nose hits the ground at G such that the javelin is almost tangent to the path of the center of mass at G. Neglect the air drag and lift on the javelin.

- Given that the javelin is at an angle $\theta = 45^\circ$ at the highest point, find the angular velocity of the javelin. Assume the angular velocity is constant during the flight and that the javelin makes less than a full revolution.




Problem 17.1.12

17.1.1 A disk of radius R is hinged at point O at the edge of the disk, approximately as shown. It rotates counterclockwise with angular velocity $\dot{\theta} = \bar{\omega}$. A bolt is fixed on the disk at point P at a distance r from the center of the disk. A frame $x'y'$ is fixed to the disk with its origin at the center C of the disk. The bolt position P makes an angle ϕ with the x' -axis. At the instant of interest, the disk has rotated by an angle θ .

tive to C using $R(\theta)$ and the angular velocity matrix $S(\bar{\omega})$.

- e) Using $R = 30$ cm, $r = 25$ cm, $\theta = 60^\circ$, and $\phi = 45^\circ$, find $[\bar{\mathbf{r}}_{C/O}]_{xy}$, and $[\bar{\mathbf{r}}_{P/O}]_{xy}$ at the instant shown.
- f) Assuming that the angular speed is $\omega = 10$ rad/s at the instant shown, find $[\bar{\mathbf{v}}_{C/O}]_{xy}$ and $[\bar{\mathbf{v}}_{P/O}]_{xy}$ taking other quantities as specified above.



Problem 17.1

- a) Write the position vector of point P relative to C in the $x'y'$ coordinates in terms of given quantities.
- b) Write the position vector of point P relative to O in the xy coordinates in terms of given quantities.
- c) Write the expressions for the rotation matrix $R(\theta)$ and the angular velocity matrix $S(\bar{\omega})$.
- d) Find the velocity of point P rela-

4.1 Solution

a) $[\bar{\mathbf{r}}_{P/C}]_{x'y'} = \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix}$

b) $[\bar{\mathbf{r}}_{P/O}]_{xy} = [\bar{\mathbf{r}}_{C/O}]_{xy} + [R(\theta)] [\bar{\mathbf{r}}_{P/C}]_{x'y'}$

$$= \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix} + \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix}$$

c) $R(\theta) = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}$ Rotation matrix

Book $\Rightarrow$ Pg. 669 $S(\bar{\omega}) = \dot{R} R^T = \begin{bmatrix} -\bar{\omega} \sin \theta & -\bar{\omega} \cos \theta \\ \bar{\omega} \cos \theta & -\bar{\omega} \sin \theta \end{bmatrix} \begin{bmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{bmatrix}$

$$= \begin{bmatrix} \bar{\omega}(-\sin \theta \cos \theta + \sin \theta \cos \theta) & -\bar{\omega}(\sin^2 \theta + \cos^2 \theta) \\ \bar{\omega}(\cos^2 \theta + \sin^2 \theta) & \bar{\omega}(\sin \theta \cos \theta - \sin \theta \cos \theta) \end{bmatrix}$$


$$= \begin{bmatrix} 0 & -\bar{\omega} \\ \bar{\omega} & 0 \end{bmatrix}$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

16.1.1

Thursday, April 11, 2019

14:17



given: ω ccw
 θ
 ϕ

Problem 16.1.1

a) Find $[\vec{r}_{P/C}]_{x'y'}$

$$[\vec{r}_{P/C}]_{x'y'} = r \begin{bmatrix} \cos \phi \\ \sin \phi \end{bmatrix}$$

b) Find $[\vec{r}_{P/O}]_{xy}$

$$[\vec{r}_{P/O}]_{xy} = [\vec{r}_{C/O}]_{xy} + [\vec{r}_{P/C}]_{xy}$$

$$\text{where } [\vec{r}_{P/C}]_{xy} = \begin{bmatrix} x_{P/C} \\ y_{P/C} \end{bmatrix} = \begin{bmatrix} x'_{P/C} \cos \theta - y'_{P/C} \sin \theta \\ x'_{P/C} \sin \theta + y'_{P/C} \cos \theta \end{bmatrix}$$

$$= \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} x'_{P/C} \\ y'_{P/C} \end{bmatrix} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} [\vec{r}_{P/C}]_{x'y'} \quad R(\theta)$$

$$\begin{aligned} \therefore [\vec{r}_{P/O}]_{xy} &= [\vec{r}_{C/O}]_{xy} + R(\theta) \cdot [\vec{r}_{P/C}]_{x'y'} \\ &= R \begin{bmatrix} \cos \theta \\ \sin \theta \end{bmatrix} + \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} R \begin{bmatrix} \cos \phi \\ \sin \phi \end{bmatrix} \end{aligned}$$

c) Find Rotation matrix $R(\theta)$ & angular velocity matrix $S(\vec{\omega})$

$$R(\theta) \text{ see b) } R(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} \leftarrow \text{orthogonal}$$

$$\begin{aligned} S(\vec{\omega}) &= \dot{R} R^{-1} = \begin{bmatrix} -\dot{\theta} \sin\theta & -\dot{\theta} \cos\theta \\ \dot{\theta} \cos\theta & -\dot{\theta} \sin\theta \end{bmatrix} \begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix} \\ &= \begin{bmatrix} 0 & -\dot{\theta} \\ \dot{\theta} & 0 \end{bmatrix} \end{aligned}$$

d) Find $\vec{v}_{P/C}$ using $R(\theta)$ and $S(\vec{\omega})$

$$\begin{aligned} [\vec{r}_{P/C}]_{x'y'} &= S(\vec{\omega}) R(\theta) [\vec{r}_{P/C}]_{x'y'} \\ &= \begin{bmatrix} 0 & -\dot{\theta} \\ \dot{\theta} & 0 \end{bmatrix} \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} \begin{bmatrix} r \cos\phi \\ r \sin\phi \end{bmatrix} \\ &= \begin{bmatrix} -\dot{\theta} (r \cos\phi \sin\theta + r \cos\phi \cos\theta) \\ \dot{\theta} (r \cos\phi \cos\theta - r \sin\phi \sin\theta) \end{bmatrix} \end{aligned}$$

e) Find $[\vec{r}_{C/O}]_{xy}$ and $[\vec{r}_{P/O}]_{xy}$

$$\text{Given } R = 30 \text{ cm } \quad r = 25 \text{ cm } \quad \theta = 60^\circ \quad \phi = 45^\circ$$

$$[\vec{r}_{C/O}]_{xy} = R * \begin{bmatrix} \cos\theta \\ \sin\theta \end{bmatrix} = \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} \text{ [cm]}$$

$$\begin{aligned} [\vec{r}_{P/O}]_{xy} &= R * \begin{bmatrix} \cos\theta \\ \sin\theta \end{bmatrix} + \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} * r * \begin{bmatrix} \cos\phi \\ \sin\phi \end{bmatrix} \\ &= \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} + \begin{bmatrix} \frac{1}{2} & -\frac{\sqrt{3}}{2} \\ \frac{\sqrt{3}}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} \frac{25\sqrt{2}}{2} \\ \frac{25\sqrt{2}}{2} \end{bmatrix} \\ &= \begin{bmatrix} 8.53 \\ 50.13 \end{bmatrix} \text{ [cm]} \end{aligned}$$

f) Find $[\vec{v}_{C/O}]_{xy}$ and $[\vec{v}_{P/O}]_{xy}$

$$\text{Given } R, r, \theta, \phi \text{ as e) and } \omega = 10 \text{ rad/s}$$

$$[\vec{v}_{C/O}]_{xy} = [\dot{\vec{r}}_{C/O}]_{xy} = \begin{bmatrix} R \cos\theta \\ R \sin\theta \end{bmatrix} = \dot{\theta} \begin{bmatrix} -R \sin\theta \\ R \cos\theta \end{bmatrix} = \begin{bmatrix} -150\sqrt{3} \\ 150 \end{bmatrix} \text{ [cm/s]}$$

$$\begin{aligned}
 [\vec{v}_{p/o}]_{xy} &= [\dot{\vec{r}}_{p/o}]_{xy} = [\vec{v}_{c/o}]_{xy} + \dot{R}(\theta) [\vec{r}_{p/c}]_{x'y'} \\
 &= \begin{bmatrix} -150\sqrt{3} \\ 150 \end{bmatrix} + \dot{\theta} \begin{bmatrix} -\sin\theta & -\cos\theta \\ \cos\theta & -\sin\theta \end{bmatrix} \begin{bmatrix} r\cos\phi \\ r\sin\phi \end{bmatrix} \\
 &\approx \begin{bmatrix} -150\sqrt{3} \\ 150 \end{bmatrix} + \begin{bmatrix} -241.48 \\ -64.70 \end{bmatrix} [\text{cm/s}] = \begin{bmatrix} -501.29 \\ 85.30 \end{bmatrix} [\text{cm/s}]
 \end{aligned}$$

Katherine Cao

Point P relative to C in $x'y'$: $[\vec{r}_{P/C}]_{x'y'}$

$$[\vec{r}_{P/C}]_{x'y'} = \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix} = r \begin{bmatrix} \cos \phi \\ \sin \phi \end{bmatrix}$$

Point P relative to O in xy : $[\vec{r}_{P/O}]_{xy}$

$$[\vec{r}_{P/O}]_{xy} = [\vec{r}_{C/O}]_{xy} + [\vec{r}_{P/C}]_{xy}$$

$$[\vec{r}_{P/O}]_{xy} = [R(\theta)] [\vec{r}_{P/C}]_{x'y'}$$

$$\text{with } [R(\theta)] = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix}$$

$$[\vec{r}_{P/O}]_{xy} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} r \begin{bmatrix} \cos \phi \\ \sin \phi \end{bmatrix}$$

$$= r \begin{bmatrix} \cos \theta \cos \phi - \sin \theta \sin \phi \\ \sin \theta \cos \phi + \cos \theta \sin \phi \end{bmatrix}$$


$$= r \begin{bmatrix} \cos(\theta + \phi) \\ \sin(\theta + \phi) \end{bmatrix}$$

PTSS

$$[\vec{r}_{C/O}]_{xy} = \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix} = R \begin{bmatrix} \cos \theta \\ \sin \theta \end{bmatrix}$$

$$[\vec{r}_{P/O}]_{xy} = [\vec{r}_{C/O}]_{xy} + [\vec{r}_{P/C}]_{xy} \\ = R \begin{bmatrix} \cos \theta \\ \sin \theta \end{bmatrix} + r \begin{bmatrix} \cos(\theta + \phi) \\ \sin(\theta + \phi) \end{bmatrix}$$

$$[\vec{r}_{P/O}]_{xy} = \begin{bmatrix} R \cos \theta + r \cos(\theta + \phi) \\ R \sin \theta + r \sin(\theta + \phi) \end{bmatrix}$$

Alternatively, find $[\vec{r}_{P/C}]_{xy}$ 

$$[\vec{r}_{P/C}]_{xy} = \begin{bmatrix} r \sin d \\ r \cos d \end{bmatrix}$$

with $d = \phi + \theta$

see P755 10.8 & 2 b) For $S(\vec{\omega})$ see P765

$$R(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} \quad S(\vec{\omega}) = \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix}$$

or, get $S(\vec{\omega})$ from

$$S(\vec{\omega}) = \dot{R}(\theta) R(\theta)^{-1}$$

$$R(\theta) = \begin{bmatrix} -\dot{\theta}\sin\theta & -\dot{\theta}\cos\theta \\ \dot{\theta}\cos\theta & -\dot{\theta}\sin\theta \end{bmatrix}$$

since $R(\theta)$ is orthogonal

$$R(\theta)^{-1} = R(\theta)^T = \begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix}$$

$$S(\vec{\omega}) = \dot{R}(\theta) R(\theta)^{-1}$$

$$= \begin{bmatrix} -\dot{\theta}\sin\theta & -\dot{\theta}\cos\theta \\ \dot{\theta}\cos\theta & -\dot{\theta}\sin\theta \end{bmatrix} \begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix}$$

$$= \begin{bmatrix} 0 & -\dot{\theta} \\ \dot{\theta} & 0 \end{bmatrix} = \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix}$$

see P765 for details

$$[\vec{V}_{P/C}]_{xy} = [\vec{r}_{P/C}]_{xy}$$

$$= S(\vec{\omega}) [\vec{r}_{P/C}^{\text{ref}}]_{xy}$$

$$= S(\vec{\omega}) [\vec{r}_{P/C}]_{xy'}$$

$$= S(\vec{\omega}) R(\theta) [\vec{r}_{P/C}]_{xy}$$

$$= \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix} \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix} \begin{bmatrix} r\cos\phi \\ r\sin\phi \end{bmatrix}$$

$$= \begin{bmatrix} -\omega r \sin(\theta + \phi) \\ \omega r \cos(\theta + \phi) \end{bmatrix}$$

$$[\vec{V}_{P/C}]_{xy} = [\vec{r}_{P/C}]_{xy}$$

$$= \frac{d}{dt} (R(\theta) [\vec{r}_{P/C}]_{xy'})$$

$$= \dot{R}(\theta) [\vec{r}_{P/C}]_{xy'} + R(\theta) [\dot{\vec{r}}_{P/C}]_{xy'}$$

$$= S(\vec{\omega}) R(\theta) [\vec{r}_{P/C}]_{xy}$$

(Slightly more detailed math)

Given $R=30 \text{ cm}$ $r=25 \text{ cm}$

$$\theta = 60^\circ \quad \phi = 45^\circ$$

Find $[\vec{r}_{C/O}]_{xy}$, $[\vec{r}_{P/O}]_{xy}$

from b)

$$[\vec{r}_{C/O}]_{xy} = \begin{bmatrix} R\cos\theta \\ R\sin\theta \end{bmatrix} = R \begin{bmatrix} \cos\theta \\ \sin\theta \end{bmatrix}$$

$$= \begin{bmatrix} 30\cos(60^\circ) \\ 30\sin(60^\circ) \end{bmatrix} \text{ cm} = \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} \text{ cm}$$

$$[\vec{r}_{P/O}]_{xy} = \begin{bmatrix} R\cos\theta + r\cos(\theta + \phi) \\ R\sin\theta + r\sin(\theta + \phi) \end{bmatrix}$$

$$= \begin{bmatrix} 30\cos(60^\circ) + 25\cos(60^\circ + 45^\circ) \\ 30\sin(60^\circ) + 25\sin(60^\circ + 45^\circ) \end{bmatrix} \text{ cm} = \begin{bmatrix} 8.53 \\ 50.1 \end{bmatrix} \text{ cm}$$

$$[\vec{V}_{C/O}]_{xy} = S(\vec{\omega}) [\vec{r}_{C/O}]_{xy} = S(\vec{\omega}) [\vec{r}_{C/O}]_{xy}$$

$$= \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix} \begin{bmatrix} R\cos\theta \\ R\sin\theta \end{bmatrix} = \begin{bmatrix} -\omega R\sin\theta \\ \omega R\cos\theta \end{bmatrix}$$

$$= \begin{bmatrix} -(10 \text{ rad/s})(30 \text{ cm})\sin(60^\circ) \\ (10 \text{ rad/s})(30 \text{ cm})\cos(60^\circ) \end{bmatrix} = \begin{bmatrix} -150\sqrt{3} \\ 150 \end{bmatrix} \text{ cm/s}$$

$$[\vec{V}_{P/O}]_{xy} = S(\vec{\omega}) [\vec{r}_{P/O}]_{xy} = S(\vec{\omega}) [\vec{r}_{P/O}]_{xy}$$

$$= \begin{bmatrix} 0 & -\omega \\ \omega & 0 \end{bmatrix} \begin{bmatrix} R\cos\theta + r\cos(\theta + \phi) \\ R\sin\theta + r\sin(\theta + \phi) \end{bmatrix}$$

$$= \begin{bmatrix} -50.1 \\ 85.3 \end{bmatrix} \text{ cm/s}$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

$$\begin{aligned}
 d) \quad [\dot{\vec{r}}_{P/C}]_{x'y'} &= S(\dot{\theta}) R(\theta) [\vec{r}_{P/C}]_{x'y'} \\
 &= \begin{bmatrix} 0 & -\dot{\theta} \\ \dot{\theta} & 0 \end{bmatrix} \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix} \\
 &= \begin{bmatrix} -\dot{\theta} \sin \theta & -\dot{\theta} \cos \theta \\ \dot{\theta} \cos \theta & -\dot{\theta} \sin \theta \end{bmatrix} \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix} \\
 &= \begin{bmatrix} -\dot{\theta} (r \cos \phi \sin \theta + r \cos \phi \cos \theta) \\ \dot{\theta} (r \cos \phi \cos \theta - r \sin \phi \sin \theta) \end{bmatrix}
 \end{aligned}$$

$$e) \quad R = 30 \text{ cm}, \quad r = 25 \text{ cm}, \quad \theta = 60^\circ, \quad \phi = 45^\circ$$

$$\begin{aligned}
 [\vec{r}_{C/O}]_{xy} &= \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix} = \begin{bmatrix} 30 \cos 60^\circ \\ 30 \sin 60^\circ \end{bmatrix} \\
 &= \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} \text{ [cm]}
 \end{aligned}$$

$$\begin{aligned}
 [\vec{r}_{P/O}]_{xy} &= \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix} + \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \begin{bmatrix} r \cos \phi \\ r \sin \phi \end{bmatrix} \\
 &= \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} + \begin{bmatrix} 1/2 & -\sqrt{3}/2 \\ \sqrt{3}/2 & 1/2 \end{bmatrix} \begin{bmatrix} 25 \cos 45^\circ \\ 25 \sin 45^\circ \end{bmatrix} \\
 &= \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} + 25 \begin{bmatrix} \sqrt{2}/4 - \sqrt{6}/4 \\ \sqrt{6}/4 + \sqrt{2}/4 \end{bmatrix} \text{ [cm]} \\
 &= \begin{bmatrix} 8.53 \\ 50.13 \end{bmatrix} \text{ [cm]}
 \end{aligned}$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

$$f) \quad \omega = 10 \text{ rad/s}$$


$$[\vec{v}_{C/O}]_{xy} = [\vec{r}_{C/O}]_{xy} = \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix} = \dot{\theta} \begin{bmatrix} R \cos \theta \\ R \sin \theta \end{bmatrix}$$

$$= \dot{\theta} [\vec{r}_{C/O}]_{xy} = (10) \begin{bmatrix} 15 \\ 15\sqrt{3} \end{bmatrix} = \begin{bmatrix} 150 \\ 150\sqrt{3} \end{bmatrix} \text{ [cm/s]}$$

$$[\vec{v}_{P/O}]_{xy} = \dot{\theta} [\vec{r}_{P/O}]_{xy} = (10) \begin{bmatrix} 8.53 \\ 50.13 \end{bmatrix}$$

$$= \begin{bmatrix} 85.3 \\ 500.13 \end{bmatrix} \text{ [cm/s]}$$

17.1.2 A uniform rigid rod AB of length $\ell = 1 \text{ m}$ rotates at a constant angular speed ω about an unknown fixed point. At the instant shown, the velocities of the two ends of the rod are $\vec{v}_A = -1 \text{ m/s} \hat{i}$ and $\vec{v}_B = 1 \text{ m/s} \hat{j}$.



Problem 17.2

- Find the angular velocity of the rod.
- Find the center of rotation of the rod.

4.40 2

$\vec{v}_A = -1 \hat{i} \text{ m/s}, \vec{v}_B = 1 \hat{j} \text{ m/s}$
 Find: ω , center of rotation P
 Note: KINEMATICS prob., FBD not reqd.


a) $\vec{v}_B = \vec{v}_A + \vec{v}_{B/A} = \vec{v}_A + \omega \times \vec{r}_{B/A}$
 or, $\vec{v}_{B/A} = \vec{v}_B - \vec{v}_A = \omega \times \vec{r}_{B/A}$
 or $(1 \hat{i} + 1 \hat{j}) \text{ (m/s)} = \omega \times (\hat{i} - \hat{j}) \text{ (m)}$
 ASSUME $\omega = \omega \hat{k}$, planar prob.
 $\sqrt{2} (1 \hat{i} + 1 \hat{j}) \text{ (m/s)} = \omega (\hat{j} + \hat{i}) \text{ (m)}$
 $\Rightarrow \omega = 1 \text{ s}^{-1}, \boxed{\omega = \sqrt{2} \hat{k} \text{ s}^{-1}}$

b) $\vec{v}_P = \vec{v}_A + \omega \times \vec{r}_{P/A} = 0$
 Let $\vec{r}_{P/A} = a \hat{i} + b \hat{j}$
 $-1 \hat{i} \text{ (m/s)} + \sqrt{2} \hat{k} \times (a \hat{i} + b \hat{j}) \text{ s}^{-1}$
 $= -1 \hat{i} \text{ (m/s)} + \sqrt{2} a \hat{j} \text{ s}^{-1} - \sqrt{2} b \hat{i} \text{ s}^{-1} = 0$
 $\Rightarrow \boxed{a = 0 \text{ m}, b = -\frac{1}{\sqrt{2}} \text{ m}}$
 $\boxed{\vec{r}_P = \vec{r}_A - \frac{1}{\sqrt{2}} \hat{j} \text{ m}}$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

17.1.3 A square plate ABCD rotates at a constant angular speed about an unknown point in its plane. At the instant shown, the velocities of the two corner points A and D are $\vec{v}_A = -2\text{ ft/s}(\hat{i} + \hat{j})$ and $\vec{v}_D = -(2\text{ ft/s})\hat{i}$, respectively.

- Find the center of rotation of the plate.
- Find the acceleration of the center of mass of the plate.



Problem 17.3

Coordinates of A $(0, l)$; $l\hat{j}$
 " " D (l, l) ; $l(\hat{i} + \hat{j})$
 Let the " " O' [center] ; $(a\hat{i} + b\hat{j})$

Center O' has zero velocity.
 Position vectors of points A and D w.r.t. O' are
 $\vec{O'A}$ & $\vec{O'D}$ respectively.

$\vec{O'A} \perp \vec{v}_A$ $\odot \vec{O'A} = \vec{OA} - \vec{OO'}$
 $\vec{O'D} \perp \vec{v}_D$ $= (-a)\hat{i} + (l-b)\hat{j}$
 $\odot \vec{O'D} = \vec{OD} - \vec{OO'}$
 $= (l-a)\hat{i} + (l-b)\hat{j}$

$\vec{O'A} \cdot \vec{v}_A = 0 \Rightarrow [-a\hat{i} + (l-b)\hat{j}] \cdot [-2\hat{i} - 2\hat{j}] = 0$
 $\Rightarrow 2a - 2l + 2b = 0$
 $\Rightarrow \boxed{a - l + b = 0}$

$\vec{O'D} \cdot \vec{v}_D = 0 \Rightarrow [(l-a)\hat{i} + (l-b)\hat{j}] \cdot [-2\hat{i}] = 0$
 $\Rightarrow -2l + 2a = 0$
 $\Rightarrow \boxed{l = a}$

$\therefore b = 0$

(a) $\therefore$ center O' is at $l\hat{i}$.

(b) Angular velocity of the plate? Let's $\omega = \omega_0 \hat{k}$ (rotating in xy plane)

$$\vec{v}_D = \vec{v}_A + \vec{\omega} \times \vec{r}_{D/A}$$

$$\Rightarrow -2\hat{i} = -2(\hat{i} + \hat{j}) + \omega_0 \hat{k} (L\hat{i})$$

$$\Rightarrow 0 = -2\hat{j} + (-\omega_0)\hat{j}$$

$$\Rightarrow 2 + \omega_0 L = 0$$

$$\Rightarrow \omega_0 = -\frac{2}{L} \text{ rad/sec}$$

velocity of center of mass?


$$\vec{v}_G = \vec{v}_A + \vec{\omega} \times \vec{r}_{G/A}$$

$$= (-2\hat{i} - 2\hat{j}) + \left(-\frac{2}{L}\right)\hat{k} \times \left(\frac{L}{2}\hat{i} - \frac{L}{2}\hat{j}\right)$$

$$= (-2\hat{i} - 2\hat{j}) + \hat{j} - \hat{i}$$

$$= -3(\hat{i} + \hat{j})$$

Acceleration of the center of mass?



$$\vec{a}_G = \vec{a}_A + \vec{a}_{G/A}$$

$$= \vec{a}_A + \vec{\omega} \times \vec{r}_{G/A} - \omega^2 \vec{r}_{G/A}$$

$\downarrow$
0

$\downarrow$
[const. angular velocity; given]

$$\Rightarrow \vec{a}_G = -\omega^2 \vec{r}_{G/A}$$

$$\Rightarrow \vec{a}_G = -\left(\frac{2}{L}\right)^2 \left[-\frac{L}{2}\hat{i} + \frac{L}{2}\hat{j}\right]$$

$$= \frac{2}{L} [\hat{i} - \hat{j}]$$

17.1.4 A ten foot ladder is leaning between a floor and a wall. The top of the ladder is sliding down the wall at one foot per second. (The foot is simultaneously sliding out on the floor). When the ladder makes a 45 degree angle with the vertical what is the speed of the midpoint of the ladder?

6.1.4

$$\vec{v}_A = (-1 \text{ ft/sec}) \hat{j}$$

$$\vec{v}_B = v \hat{i}$$

Angular velocity of ladder?

$$\vec{v}_B = \vec{v}_A + \vec{\omega} \times \vec{r}_{B/A}$$

$$\Rightarrow v \hat{i} = -1 \hat{j} + \omega_0 \hat{k} \times \left[\frac{10}{\sqrt{2}} \hat{i} - \frac{10}{\sqrt{2}} \hat{j} \right]$$

$$\Rightarrow v \hat{i} = -1 \hat{j} + \omega_0 \frac{10}{\sqrt{2}} \{ \hat{j} + \hat{i} \}$$

$$(\omega_0) \frac{10}{\sqrt{2}} - 1 = 0$$

$$\Rightarrow \omega_0 = \frac{\sqrt{2}}{10} \text{ rad/sec}$$

Velocity of midpoint G:

$$\vec{v}_G = \vec{v}_A + \vec{\omega} \times \vec{r}_{G/A}$$

$$= \vec{v}_A + \vec{\omega} \times \vec{r}_{G/A}$$


$$= -1 \hat{j} + \frac{\sqrt{2}}{10} \hat{k} \times \frac{10}{\sqrt{2}} (\hat{i} - \hat{j})$$

$$= -\hat{j} + \hat{k} \times (\hat{i} - \hat{j})$$


$$= -\hat{j} + (\hat{j} + \hat{i})$$

$$= \hat{i}$$

$$\Rightarrow \vec{v}_G = 1 \text{ ft/sec along } +ve \ x \text{ direction.}$$




17.1.5 The slender rod AB rests against the step of height h , while end "A" is moved along the ground at a constant velocity v_0 . Find $\dot{\phi}$ and $\ddot{\phi}$ in terms of x , h , and v_0 . Is $\dot{\phi}$ positive or negative? Is $\ddot{\phi}$ positive or negative?



Problem 17.5

2
16.1.5



$$\tan \phi = \frac{h}{x}$$

$$\Rightarrow \phi = \tan^{-1}\left(\frac{h}{x}\right)$$

$$\Rightarrow \frac{d\phi}{dt} = \frac{1}{1 + \left(\frac{h}{x}\right)^2} \times \frac{x \cdot \frac{dh}{dt} - h \frac{dx}{dt}}{x^2}$$

$$= \frac{1}{x^2 + h^2} \times -h \frac{dx}{dt}$$

$$\Rightarrow \frac{d\phi}{dt} = \frac{-h v_0}{x^2 + h^2}$$

Denominator $\rightarrow +ve$

$v_0 \rightarrow +ve$

$h \rightarrow +ve$

$\therefore \dot{\phi} \rightarrow -ve.$


$$\frac{d^2\phi}{dt^2} = \frac{-h v_0 \left[-2x \frac{dx}{dt} \right]}{(x^2 + h^2)^2} = \frac{2h x v_0^2}{(x^2 + h^2)^2}$$

$\Rightarrow \ddot{\phi} \Rightarrow +ve.$

17.1.6 Consider the motion of a rigid ladder which can slide on a wall and on the floor as shown in the figure. The point A on the ladder moves parallel to the wall. The point B moves parallel to the floor. Yet, at a given instant, both have velocities that are consistent with the ladder rotating about some special point, the center of rotation (COR). Define appropriate dimensions for the problem.

- a) Find the COR for the ladder when it is at some given position (and moving, of course). [Hint: if a point A is 'going in circles' about another point C, that other point C must be in the direction perpendicular to the motion of A.

- b) As the ladder moves, the COR changes with time. What is the set of points on the plane that are the COR's for the ladder as it falls from straight up to lying on the floor?



Problem 17.6

CHAPTER 16

Q
17.1.6

Length of ladder L .

$\vec{v}_A \Rightarrow$ along $-j$
 $\vec{v}_B \Rightarrow$ along i

Lines perpendicular to the velocities $\vec{v}_A$ & $\vec{v}_B$ intersect at C.



Hence C is center of rotation [COR]

co-ordinates of C w.r.t. origin O are $(L \cos \theta, L \sin \theta)$

(a) $\therefore \vec{r}_C = L [\cos \theta \hat{i} + \sin \theta \hat{j}]$

As the ladder falls from straight up to lying on the floor θ varies from 90° to 0° .

- b) The locus of center C will be quarter of a circle present in the first quadrant of co-ordinate axes.



17.1.7 A car driver on a very boring highway is carefully monitoring her speed. Over a one hour period, the car travels on a curve with constant radius of curvature, $\rho = 25$ mi, and its speed increases uniformly from 50 mph to 60 mph. What is the acceleration of the car half-way through this one hour period, in path coordinates?

①
16.1.7

Acceleration in path coordinates:

$$\vec{a} = a_t \hat{e}_t + a_n \hat{e}_n$$

$$a_t = \dot{v} \quad a_n = \frac{v^2}{\rho}$$

$$\dot{s}_A = 50 \text{ mph}$$

$$\dot{s}_B = 60 \text{ mph}$$

$$\dot{s}_B = \dot{s}_A + a_t T$$

$$\Rightarrow a_t = \frac{60 - 50}{1} = 10 \text{ miles/hour}^2$$

Total distance travelled


$$\begin{aligned} s_{\text{total}} &= \dot{s}_A T + \frac{1}{2} a_t T^2 \\ &= 50 \times 1 + \frac{1}{2} \times 10 \times 1^2 \\ &= 55 \text{ miles.} \end{aligned}$$

Velocity at half way:

$$\begin{aligned} \dot{s}_C^2 &= \dot{s}_A^2 + 2 \cdot a_t \cdot s_{1/2} \\ &= 50^2 + 2 \cdot 10 \cdot \frac{55}{2} \\ &= 2500 + 550 \\ &= 3050 \end{aligned}$$

Acceleration at C:

$$\begin{aligned} \vec{a} &= a_t \hat{e}_t + a_n \hat{e}_n \\ &= 10 \hat{e}_t + \frac{3050}{25} \hat{e}_n \\ &= 10 \hat{e}_t + 122 \hat{e}_n \text{ miles/hr}^2 \end{aligned}$$




17.1.8 The bar AB shown in the figure is 1 m long. The end A of the bar is dragged to the left on the horizontal floor at a constant speed $v_0 = 0.2$ m/s. The other end of the bar drags along the inclined plane that makes an angle $\phi = 60^\circ$ with the horizontal.

- Does the end B of the rod also have a constant speed? Does it imply that the rod has a constant angular velocity? Guess your answer and write down your reasoning. No calculations.
- Find an expression for the angular velocity of the rod in terms of θ , ϕ ,

ℓ , and v_0 .

- Find the velocity of end B when $\theta = 30^\circ$.




Problem 17.8

Answer:

$$(b) \vec{\omega} = -\frac{v_0 \sin \phi}{\ell \cos(\phi - \theta)} \hat{k}$$

17.1.10 A rod AC of length $\ell = 2$ m is mounted on a cart at point C. The cart slides down under gravity on a frictionless surface inclined at $\phi = 45^\circ$ from the horizontal. Assume that bar has negligible mass compared to that of the cart. The cart is released from rest and it reaches the position shown in $t = 2$ s. At the instant shown, $\theta = 60^\circ$, and rod AC has an angular velocity $\dot{\omega} = 0.5 \text{ rad/s} \hat{k}$ and angular acceleration $\ddot{\alpha} = 1 \text{ rad/s}^2 \hat{k}$.

Find the velocity and acceleration of the center of mass of the rod at the instant shown.



Problem 17.10

Q

16.1.10

11

Acceleration of the cart $= g/\sqrt{2}$

velocity of the cart at the position shown

$$v_c = u + at$$

$$= 0 + \frac{g}{\sqrt{2}} \cdot 2$$

$$\Rightarrow v_c = \sqrt{2}g \text{ m/s}$$

The co-ordinate axes are chosen as shown.

Velocity of the center of mass of the rod:

$$\vec{v}_{cm} = \vec{v}_c + \vec{\omega}_{rod} \times \vec{r}_{cm/c}$$

$$\text{Hence } \vec{v}_c = \sqrt{2}g \hat{i} \text{ m/s}$$

$$\vec{\omega}_{rod} = 0.5 \hat{k} \text{ rad/s}$$

$$\vec{r}_{cm/c} = \frac{\ell}{2} [-\cos 75^\circ \hat{i} + \sin 75^\circ \hat{j}]$$

$$= \frac{\ell}{2} [-0.258 \hat{i} + 0.966 \hat{j}]$$

$$= -0.258 \hat{i} + 0.966 \hat{j} \text{ m} \quad [\because \ell = 2 \text{ m}]$$

$$\therefore \vec{v}_{cm} = \sqrt{2}g \hat{i} + 0.5 \hat{k} \times [-0.258 \hat{i} + 0.966 \hat{j}]$$

$$= 13.87 \hat{i} + 0.129 (-\hat{j}) + 0.483 (-\hat{i})$$

$$= [13.387 \hat{i} - 0.129 \hat{j}] \text{ m/s}$$

Acceleration of the center of mass of the rod:



$$\vec{a}_{cm} = \ddot{\alpha} \times \vec{r}_{cm/c} + \vec{\omega}_{rod} \times (\vec{\omega}_{rod} \times \vec{r}_{cm/c})$$

$$= 1 \hat{k} \times [-0.258 \hat{i} + 0.966 \hat{j}] + 0.5 \hat{k} \times [0.5 \hat{k} \times (-0.258 \hat{i} + 0.966 \hat{j})]$$

$$= -0.258 \hat{j} - 0.966 \hat{i} + 0.5 \hat{k} \times [-0.129 \hat{j} + 0.483 \hat{i}]$$

$$= -0.258 \hat{j} - 0.966 \hat{i} + 0.0648 \hat{i} - 0.2415 \hat{j}$$


$$= -0.9012 \hat{i} - 0.4995 \hat{j} \text{ m/s}^2$$



17.1.11 A vertical bar pendulum AB of length $\ell = 4$ ft is mounted on a cart at point A. The cart has a motor that drives the bar pendulum back and forth about the vertical position such that $\theta(t) = \theta_0 \sin \omega t$ where $\theta_0 = \pi/6$ and $\omega = \pi$ rad/s. The cart moves at a constant speed $v_0 = 2$ ft/s on a sinusoidal track represented by $y(x) = y_0 \sin \lambda x$ where $y_0 = 0.5$ ft and $\lambda = \pi/4$ ft.

- Find the velocity of point B when $\theta = 0$.
- Find and plot the position of point B for one full oscillation of the bar,

assuming the bar starts from its leftmost angular position (that is, $\theta = -\theta_0$) when the cart is on one of the crests of the track.



Problem 17.11

16.1.11

$$\vec{v}_B = \vec{v}_A + \vec{\omega}_{AB} \times \vec{r}_{AB}$$

$$= 2\hat{i} + \frac{\pi^2}{6} \cos(\pi t - \frac{\pi}{2}) \hat{k} \times 4\hat{j}$$

$$\theta(t) = \theta_0 \sin \omega t$$

$$\Rightarrow \dot{\theta}(t) = (\theta_0 \omega) \cos \omega t$$

$$\Rightarrow \omega_{AB} = \frac{\pi^2}{6} \cos \pi t$$

$$\text{Hence at } t=0 \quad \theta(t) = -\theta_0 = -\frac{\pi}{6}$$

$$\therefore \theta(t) = \theta_0 \sin(\omega t - \frac{\pi}{2}) = \frac{\pi}{6} \sin(\pi t - \frac{\pi}{2})$$

Now ω_{AB} modifies to

$$\vec{\omega}_{AB} = \frac{\pi^2}{6} \cos(\pi t - \frac{\pi}{2}) \hat{k}$$

@ velocity of point B when $\theta = 0$?

time at $\theta = 0$?

$$0 = \frac{\pi}{6} \sin(\pi t - \frac{\pi}{2})$$

$$\Rightarrow \pi t - \frac{\pi}{2} = 0 \Rightarrow t = \frac{1}{2} \text{ sec.}$$

$$\vec{\omega}_{AB} \Big|_{t=\frac{1}{2}} = \frac{\pi^2}{6} \cos \pi / 6$$

$$\vec{r}_{AB} \Big|_{\theta=0} = 4 \hat{j} \text{ ft.}$$

$$\text{At } t = \frac{1}{2}, \text{ horizontal distance covered by the cart} \\ = v_0 \times \frac{1}{2} = 2 \times \frac{1}{2} = 1 \text{ ft.}$$

y-co-ordinate of the sinusoidal track at $x=1$ ft.

$$y(x) = y_0 \sin(\lambda x + \frac{\pi}{2}) \quad [\because \text{the cart starts from a crest}]$$



$$= (0.5) \sin(\frac{\pi}{4} + \frac{\pi}{2}) = \frac{1}{2\sqrt{2}} \text{ ft}$$

At point $(1, \frac{1}{2\sqrt{2}})$ slope (direction of $\vec{v}_A$):

$$y'(x) \Big|_{x=1} = y_0 \lambda \cos(\lambda x + \frac{\pi}{2})$$

$$= (0.5 \times \frac{\pi}{4}) \cos(\frac{\pi}{4} + \frac{\pi}{2})$$

$$= -0.2776$$



Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

Q

16.1.11 contd...

(13)

$$\tan^{-1}(\kappa) = -0.2776$$

$$\Rightarrow \alpha = -15.51^\circ$$

$$v_A \cos \alpha = 2 \text{ ft/sec}$$

$$\Rightarrow v_A \cos(15.51) = 2$$

$$\Rightarrow v_A = 2.076 \text{ ft/sec}$$

$$\begin{aligned} \vec{v}_A &= (v_A \cos \alpha) \hat{i} + (v_A \sin \alpha) \hat{j} \\ &= 2 \hat{i} - 0.55 \hat{j} \end{aligned}$$

 $\vec{v}_B$?

$$\begin{aligned} \vec{v}_B &= \vec{v}_A + \vec{\omega}_{AB} \times \vec{r}_{AB} \\ &= (2 \hat{i} - 0.55 \hat{j}) + \frac{\pi^2}{6} \cos\left(\pi \cdot \frac{1}{2} - \frac{\pi}{2}\right) \hat{k} \times (4 \hat{j}) \\ &= 2 \hat{i} - 0.55 \hat{j} + \frac{\pi^2}{6} \times 4 \hat{i} \\ &= (-4.58 \hat{i} - 0.55 \hat{j}) \text{ ft/s} \end{aligned}$$

(b) Locus of point B:

$$\vec{r}_B = \vec{r}_A + \vec{r}_{B/A}$$

$$\begin{aligned} \vec{r}_A &= 2t \hat{i} + 0.5 \sin\left[\frac{\pi}{4}(t+1) + \frac{\pi}{2}\right] \hat{j} \\ &= 2t \hat{i} + \frac{1}{2} \sin \frac{\pi}{2}(t+1) \hat{j} \end{aligned}$$


$$\vec{r}_{B/A} = AB \sin \theta \hat{i} + AB \cos \theta \hat{j}$$

$$= 4 \left[\frac{\pi}{6} \sin\left(\pi t - \frac{\pi}{2}\right) \right]$$

$$\begin{aligned} &= 4 \sin\left[\frac{\pi}{6} \sin\left(\pi t - \frac{\pi}{2}\right)\right] \hat{i} + 4 \cos\left[\frac{\pi}{6} \cos\left(\pi t - \frac{\pi}{2}\right)\right] \hat{j} \\ &= 4 \sin\left[-\frac{\pi}{6} \cos(\pi t)\right] \hat{i} + 4 \cos\left[\frac{\pi}{6} \sin(\pi t)\right] \hat{j} \end{aligned}$$

17.1.12 The center of mass of a javelin travels on a more or less parabolic path while the javelin rotates during its flight. In a particular throw, the velocity of the center of mass of a javelin is measured to be $\bar{v}_C = 10 \text{ m/s}$ when the center of mass is at its highest point $h = 6 \text{ m}$. As the javelin lands on the ground, its nose hits the ground at G such that the javelin is almost tangent to the path of the center of mass at G. Neglect the air drag and lift on the javelin.


find the angular velocity of the javelin. Assume the angular velocity is constant during the flight and that the javelin makes less than a full revolution.



Problem 17.12

- a) Given that the javelin is at an angle $\theta = 45^\circ$ at the highest point,

14.12



- Ignore the length of the javelin in calculation
- Consider linear motion, solve for ϕ and time to hit ground (t)
- Solve for angular speed using ϕ and t .

for projectile motion:

$$h = \frac{1}{2} g t^2 \Rightarrow t = \sqrt{\frac{2h}{g}} = \sqrt{\frac{2 \times 6}{10}}$$

$$\Rightarrow t = 1.1 \text{ s}$$

$$\phi = \tan^{-1}\left(\frac{v_x}{v_y}\right) = \tan^{-1}\left(\frac{v_C}{gt}\right) = \tan^{-1}\left(\frac{10}{10 \times 1.1}\right)$$

$$\Rightarrow \phi = 0.7378$$

$$\text{Total angle turned from figure above} = \frac{\pi}{4} + \left(\frac{\pi}{2} - \phi\right) = 1.62$$

$$\text{Angular velocity, } \omega = \frac{\text{Angle turned}}{\text{time taken}} = \frac{1.62}{1.1}$$


$$\boxed{\omega = 1.47 \text{ rad/s}}$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

16.1.12 The center of mass of a javelin travels on a more or less parabolic path while the javelin rotates during its flight. In a particular throw, the velocity of the center of mass of a javelin is measured to be $\vec{v}_C = 10 \text{ m/s} \hat{i}$ when the center of mass is at its highest point $h = 6 \text{ m}$. As the javelin lands on the ground, its nose hits the ground at G such that the javelin is almost tangent to the path of the center of mass at G. Neglect the air drag and lift on the javelin.


- a) Given that the javelin is at an angle $\theta = 45^\circ$ at the highest point, find

the angular velocity of the javelin. Assume the angular velocity is constant during the flight and that the javelin makes less than a full revolution.



Filename: pfigure14-1-javelin
Problem 16.1.12

Free body diagram:



Linear momentum balance: $m\vec{a} = \sum \vec{F} = -mg\hat{j}$

Take the moment that the center of mass is at its highest point (point C) as $t=0$ and integrate the LMB, we get

$$v_x = \text{const.} = v_x(0) = \vec{v}_C \cdot \hat{i} = 10 \text{ m/s}$$

$$v_y = \int -g dt = -gt + v_y(0) = -gt + \vec{v}_C \cdot \hat{j} = -gt$$

$$y = \int -v_y dt = -\frac{1}{2}gt^2 + y(0) = -\frac{1}{2}gt^2 + h$$

The time the javelin gets to point G is

$$y = -\frac{1}{2}gt^2 + h = 0 \rightarrow t_G = \sqrt{\frac{2h}{g}} = 1.106 \text{ s}$$

At t_G , $v_x = 10 \text{ m/s}$, $v_y = -gt = -\sqrt{2gh} = -10.84 \text{ m/s}$

$$\phi = \text{atan2}(|v_x|, |v_y|) = 0.7451 \text{ rad}$$

We are given that the angular velocity of the javelin is constant, so the angular velocity is

$$\omega = \frac{\pi - (\theta + \phi)}{t_G} = 1.456 \text{ rad/s (clockwise) or}$$

$$\omega = \frac{\theta + \phi}{t_G} = 1.383 \text{ rad/s (counterclockwise)}$$


MAE2030 HW P54 (17.1.12) Solution

Duan Li

17.1.12 The center of mass of a javelin travels on a more or less parabolic path while the javelin rotates during its flight. In a particular throw, the velocity of the center of mass of a javelin is measured to be $\vec{v}_C = 10 \text{ m/s} \hat{i}$ when the center of mass is at its highest point $h = 6 \text{ m}$. As the javelin lands on the ground, its nose hits the ground at G such that the javelin is almost tangent to the path of the center of mass at G. Neglect the air drag and lift on the javelin.

- a) Given that the javelin is at an angle $\theta = 45^\circ$ at the highest point, find

the angular velocity of the javelin. Assume the angular velocity is constant during the flight and that the javelin makes less than a full revolution.




Problem 17.1.12

Given: $\vec{v}_C(t=0)$, h , $\theta(t=0)$, constant angular velocity

Define time $t = 0$ to be when the center of mass is at point C

Find: angular velocity

Free body diagram



Define point P to be the center of mass of the javelin

Linear momentum balance

$$m\vec{a} = \sum \vec{F} = -mg\hat{j}$$

Initial conditions

$$v_x(0) = \vec{v}_C \cdot \hat{i} = 10 \text{ m/s}$$

$$v_y(0) = \vec{v}_C \cdot \hat{j} = 0 \text{ m/s}$$

$$y(0) = h = 6 \text{ m}$$

Solve the LMB

$$\{m\vec{a} = -mg\hat{j}\} \cdot \hat{i} \rightarrow ma_x = 0$$

$$v_x = \int a_x dt = \int 0 dt = C_1$$

$$v_x(0) = C_1 = 10 \text{ m/s}$$

$$\rightarrow v_x = 10 \text{ m/s}$$

$$\{m\vec{a} = -mg\hat{j}\} \cdot \hat{j} \rightarrow ma_y = -mg$$

$$v_y = \int a_y dt = \int -g dt = -gt + C_2$$

$$v_y(0) = C_2 = 0 \text{ m/s}$$

$$\rightarrow v_y = -gt$$

$$y = \int v_y dt = -\frac{1}{2}gt^2 + C_3$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.

MAE2030 HW P54 (17.1.12) Solution

Duan Li

$$y(0) = C_3 = h$$

$$\rightarrow y = -\frac{1}{2}gt^2 + h$$

The time the javelin gets to point G is

$$y = -\frac{1}{2}gt_G^2 + h = 0 \text{ m}$$

$$\rightarrow t_G = 1.11 \text{ s}$$


The velocity at point G

$$v_x(t_G) = 10 \text{ m/s} = v_{Gx}$$

$$v_y(t_G) = -gt_G = -10.8 \text{ m/s} = v_{Gy}$$

$$\rightarrow \vec{v}_G = v_{Gx}\hat{i} + v_{Gy}\hat{j}$$

Directions of the javelin and of the path at point G



The direction of the javelin at point G

$$\hat{e}_r = \sin \phi \hat{i} - \cos \phi \hat{j}$$

The tangent direction of the path at point G is $\frac{\vec{v}_G}{|\vec{v}_G|}$
 (Velocity is always tangent to the path.)


According to the problem, at point G, the javelin is tangent to the path, so

$$\hat{e}_r \times \vec{v}_G = \vec{0}$$

$$\sin \phi v_{Gy} \hat{k} + \cos \phi v_{Gx} \hat{k} = \vec{0}$$

$$\rightarrow \phi = \arctan\left(-\frac{v_{Gx}}{v_{Gy}}\right) = 0.745 \text{ rad}$$

Examples of possible javelin motion




According to the problem, the angular velocity of the javelin is constant and the javelin makes less than a full revolution, so there are 4 possible cases (shown below).

The javelin motion is drawn by denoting the two ends A and B moving to new locations A' and B'.

Case 1. the javelin rotates CCW by a small angle


MAE2030 HW P54 (17.1.12) Solution

Duan Li




$$\vec{\omega}_1 = \frac{\phi + \theta}{t_G} \hat{k} = 1.38 \text{ rad/s } \hat{k}$$

Case 2. the javelin rotates CCW by a large angle




$$\vec{\omega}_2 = \frac{\phi + \theta + \pi}{t_G} \hat{k} = 4.21 \text{ rad/s } \hat{k}$$

Case 3. the javelin rotates CW by a small angle



$$\vec{\omega}_3 = \frac{\pi - \phi - \theta}{t_G} (-\hat{k}) = -1.45 \text{ rad/s } \hat{k}$$

Case 4. the javelin rotates CW by a large angle



$$\vec{\omega}_4 = \frac{2\pi - \phi - \theta}{t_G} (-\hat{k}) = -4.28 \text{ rad/s } \hat{k}$$

Disclaimer: We have lost track of the many people who wrote these solutions. They are not official and have not been reviewed by the authors for correctness.